

Orange Projoint Tape



Product Specification

Adhesion to Steel Plate	10.5 N/cm / 95.9 oz/in
Elongation at Break	20 %
Tensile Strength	39 N/cm / 22.3 Lbs/in
Thickness	165 µm / 6.5 mils
Weight (g/m2)	154 g/m2

Handling & Storage

- Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape should be used within 12 months from date of shipment. We do not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Features & Benefits

- Easy tear
- 48mm x 50m
- Suitable for multiple surfaces
- Waterproof

Applications

- Bundling, sealing, temporary repairing operations
- Pipe wrapping and duct seaming
- Double glazing unit sealing
- General maintenance and protection
- Color coding and marking

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Orange Projoint Tape 07 February 2026



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

