


# PeelGard® One Coat



**Introducing our protective solution that adapts to provide tailored defense in a single application, effectively minimizing potential damage. Ideal for both residential and commercial environments, it acts as a strong shield, reducing failure costs.**

**With an environmentally friendly, water-based, and non-flammable formula, it ensures protection without harm. Its gentle nature preserves material integrity, and easy residue-free removal simplifies maintenance. UV resistance guarantees long-lasting effectiveness.**

**Suitable for a wide range of applications, our product embodies efficiency, durability, and sustainability.**

**This solution is compatible with all types of glass, ceramics, concrete, various metals, and other coated, non-absorbing surfaces. Level of coverage is dependant on usage covering from 80sqm for external heavy duty protection up to 200sqm for light protection.**

## Features & Benefits

- Adapts to provide tailored defense in a single application
- Minimizes potential damage during construction and transportation
- Environmentally friendly, water-based, and non-flammable formula
- Easy, residue-free removal for simplified maintenance
- Suitable for glass, ceramics, concrete, various metals, and coated, non-

**0800 834 704 | 01625 855600**  
**enquiries@protection.co.uk**  
**www.protection.co.uk**

## Product Specification

Colour	Translucent
Density	1,0-1,1
Water Resistant	Yes

## Installation Instructions/Guidelines

- Stir well before use. PeelGard One Coat must have a sufficient layer thickness for easy removal (minimum 100 micron wet). For long-term protection, apply a 200-micron layer. Apply with roller or airless sprayer. Do not change the product composition. For easy removal, steer away from rubbers or sharp edges, or make sure to have sufficient layer thickness. Be careful using PeelGard One Coat on soiled, frozen, etched, or coated glass. Remove cleaning product residue, cement, glue etc. before applying PeelGard One Coat. If protecting window frames and rubbers, apply a thicker layer of PeelGard. Removal of PeelGard One Coat can commence after 6 hours. Prevent contact with absorbing materials. Use only in well ventilated areas. Touchable after maximum 1 hour, completely cured within 24 hours (depending on temperature).
- Please contact our technical team for specific advice

## Handling & Storage

- Shelf life if unopened minimum 12 months. Store frost-free in a dry and cool place. Keep container tightly closed.



## PRODUCT DATA SHEET

0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk



## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: PeelGard® One Coat 22 January 2026



0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

