

# Protec General Purpose Jointing Tape



Our printed tape is a versatile and practical jointing solution. Featuring medium to high tack, it's ideal for seamlessly joining temporary protection materials such as Proplex Plastic Sheets and Protec Flooring Rolls.

Please be aware that the tape's performance may be affected by extreme temperatures; for instance, sub-zero freezing conditions can reduce adhesion, while excessively high temperatures might leave adhesive residue on surfaces.

We always recommend conducting a trial application on finished surfaces to test suitability before full use. For guidance and specific inquiries, please reach out to our technical team for expert advice. For projects involving veneer doors, we suggest using our protective Door Sleeves instead of tape.

If you would like samples of any of our adhesive tapes, please don't hesitate to call us at 0800 834 704!

## Features & Benefits

- Practical, general purpose jointing tape with medium-high tack.
- Ideal for joining temporary protection materials, such as Proplex Plastic Sheets and Protec Flooring Rolls.
- Not suitable for veneer doors; protective Door Sleeves are recommended for this application.
- Available for custom printing.

0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

## Product Specification

Colour	White
Material	Hot Melt Polypropylene
Thickness	32 micron
Weight Per Roll	0.17kg

## Range

Code	Size
PROTAPE50X66	50mm x 66m

## Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test suitability
- Please contact our technical department for specific advice

## Handling & Storage

- Store in ambient conditions. Please note the performance of tape varies in extreme temperatures, subzero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the tape is removed.



# PRODUCT DATA SHEET

---



## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [Protec General Purpose Jointing Tape](#) 25 May 2026



0800 834 704 | 01625 855600  
[enquiries@protection.co.uk](mailto:enquiries@protection.co.uk)  
[www.protection.co.uk](http://www.protection.co.uk)

