

# High Performance Low Tack Tape



High Performance Low Tack Tapes leaves no residue for up to 6 months. It is available in two sizes and is ideal for fixing protection in place on delicate or finished surfaces.

It is fully recyclable unlike most low tac tapes that are made from PVC.

Before Applying tape to finished surfaces, we always recommend carrying out a trial to test suitability. Please ring our technical staff for specific advice. We do not recommend applying tape to veneer doors and recommend the use of our protective Door Sleeves for this application. Should you require samples of any of our adhesive tapes, please call on 0800 834 704!

## Features & Benefits

- Leaves no residue for up to six months
- Avoid costly clean up time when removing adhesive residue from finished surfaces
- Waterproof and UV resistant for up to 3 months so can be used in direct sunlight without affecting performance
- Ideal for fixing protection in place on finished surfaces
- Often used as a barrier to halt dirt ingress underneath protection materials

## Product Specification

Adhesive	Acrylic Clear Adhesive
Colour	Light Blue
Material	Bamboo Composite
Recycled Content	Yes
Temperature Application Range	-10C > +40C
Thickness	85
Tolerance	±10
UV Resistant	3 months
Water Resistant	Yes

## Range

Code	Size	Pack Qty
TOUGHSPECLOW48MM	48mm x 33m	24
TOUGHSPECLOW75MM	75mm x 33m	16

## Installation Instructions/Guidelines

- Before applying any adhesive tape to finished surfaces, we recommend trialing a small amount as a test.
- Clean the area to be protected
- Peel back edge of High Performance Low Tac Tape and begin to unroll
- Press down edge at beginning of area to be secured then continue applying and smoothing down the tape until temporary protection is secure
- Carefully cut end with a sharp edge. When finished, peel away and recycle or discard

## Handling & Storage

- Must be stored in a dry location, protected from direct sunlight and freezing. Storage temperature should be close to room temperature (15°C – 25°C), relative humidity of 60%.
- When stored below 10°C it is recommended to allow the tape to climatize to room temperature before use.
- Shelf life from date of manufacture is 12 months.
- Test product in a discrete area first.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: High Performance Low Tack Tape 10 July 2025

