

Vented Fence Screening



_	_	_	
Features	2.	Ron	ofite
realules	α	DCI	ICIIIO

- Custom printed options available to promote your brand.
- Large format design for practical and easy installation.
- 1.85m x 50m Roll
- Durable and tear-proof material to withstand harsh weather conditions.
- Vented design allows for airflow, enhancing usability.

Applications

- ◆ Heras Fence branding
- ◆ Used to obscure the view into working areas

Product Specification	
Air Permeability	Mean 586.3 CV (%) 13.4 95%
	Confidence interval (mm/s) + 48.78
Colour	White
Material	Interwoven open weave coated
	Polypropylene
Weight (g/m2)	145gsm
Weight Per Roll	15kg

Range

Code	Size
VENTEDUNPRINTED	1.85 x 50m

Installation Instructions/Guidelines

- Assess the fencing to ensure the Heras is suitable for this product and adequately anchored
- Secure the Vented Fencing rolls to the Heras fencing top and bottom with cable ties
- Fix with cable ties at least every 1m
- Regularly check the product and the fence to ensure it remains safe

Handling & Storage

• Store in ambient conditions.















Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Vented Fence Screening 26 November 2025

















