

White Low Tack Tape



Range

Code	Size
WHITELOWTAC33M	50mm x 33m
WHITELOWTAC75MM	75mm x 33m

Sticks, joints and masks to most finished surfaces.

Please note, performance may be effected when used in extreme temperatures. For example, sub zero/freezing temperatures may cause lower levels of adhesions, whilst extremely high temperatures can result in stick adhesive residue.

Always trial our Low Tack Tape before applying it to your full surface. We do not recommend applying tape to veneer doors and recommend the use of our protective Door Sleeves for this application.

Features & Benefits

- No residue when removed.
- Perfect for delicate surfaces.
- Ideal for duo-toning stencil work.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [White Low Tack Tape 15 May 2026](#)



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

