

White Polythene Tape



A polythene film coated with a clean peel, dispersion acrylic adhesive.

Features & Benefits

- 50mm x 33m
- Easy tear
- Clean peel
- UV and frost-resistant
- Medium tack

Product Specification

Colour	White
Material	Polythene film, dispersion acrylic adhesive
Thickness	0.11mm

Range

Code	Size	Pack Qty
WHTPOLYTAPE500X33	50mm x 33m	1

Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test the suitability.
- We do not recommend applying any tape to veneer surfaces.
- Please contact our technical department for specific advice.
- Ensure the surface is as clean as possible before applying the tape to create the strongest seal.
- Inspect the tape at regular intervals to assess the level of adhesion.

Handling & Storage

- Store in ambient conditions.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [White Polythene Tape 31 May 2026](#)



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

