

Window Protection Film



Product Specification

Colour	Translucent
Material	Film with Acrylic Solvent Adhesive
Weight (g/m ²)	40 micron
Weight Per Roll	600mm x 25m – 1kg, 600mm x 100m – 2.9kg

Range

Code	Size
WINDOWROL600X100	600mm x 100m
WINDOWROLL600X25	600mm x 25m

Installation Instructions/Guidelines

- Before applying adhesive products to a finished surface, a trial should be undertaken to test suitability
- Please contact our technical department for specific advice
- Roll the protection out onto the window
- Apply pressure to the film to activate the adhesion
- Trim to size
- Regularly check the products and do not use for longer than 4 weeks to avoid adhesive transfer

Handling & Storage

- Store in ambient conditions Please note the performance of adhesive products varies in extreme temperatures, subzero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the product is removed.

Features & Benefits

- Resistant to moisture, sunlight and the elements.
- Self-adhesive roll negates the need for additional fixings
- Easy and quick installation
- Allows natural light to transfer into the working area
- Low adhesive level to avoid adhesive transfer

Applications

- ◆ Glazing protection
- ◆ We do not recommend for use on Pilkington Suncool™ glass or similar coated solar control product

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [Window Protection Film 04 July 2026](#)



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

