

Consumer Unit 6way HI - 100A MS+T2SPD

- PRO Metal Consumer Unit Range, suitable for residential installations
- Fully interchangeable switched and un-switched neutral pole RCBO option
- Type 2 Surge Protection Device Pre-installed & wired
- The round knockouts range are designed for the installation of round cable glands, conduits, cable grommets, and for terminating SWA final circuit cables with complete flexibility.

PRO-R06W-R1S

TECHNICAL DATA

Rated Operating Voltage (Ue)	230V~
Rated Frequency (Fn)	50/60Hz
Phase	1
Rated insulation voltage (Ui)	300V
Rated Impulse Withstand Voltage (Uimp)	4kV
Earthing System(s)	TN-S, TN-C-S-(PME), TT
Manufacturing Material	Mild Steel
Useable Ways	6
Method of Mounting	Wall Mounting
Modular Ways	9
Impact Resistance (IK)	IK05
Ingress Protection Rating	IP2XC
Finish Colour	White RAL 9003

REGISTRY

Barcode	5026992000137
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Dimensions (HWD)	28 x 11.5 x 23 mm
Pkg. level 1 - Volume (dm^3)	7.406
Pkg. level 1 - Gross weight (kg)	2.851
Pkg. level 1 - Carton Weight (kg)	0.175
Pkg. level 1 - Packaging Material	Inner Corrugated Box
Pkg. level 2 - Dimensions (HWD)	57 x 49 x 25 mm
Pkg. level 2 - Volume (dm^3)	69.825
Pkg. level 2 - Gross Weight (kg)	23.91
Pkg. level 2 - Carton Weight (kg)	1

Lewden Ltd., Unit 4, Bradbury, Drive, Springwood Industrial Estate, Braintree, Essex, CM7

Tel +44 (0)1376 336200, www.lewden.com, Sales@lewden.co.uk