



Consumer Unit 8way HI - 100A MS+T2SPD

- PRO Metal Consumer Unit Range, suitable for residential installations
- Fully interchangeable switched and un-switched neutral pole RCBO option
- Type 2 Surge Protection Device Pre-installed & wired
- The round knockouts range are designed for the installation of round cable

PRO-R08W-R1S

TECHNICAL DATA

Rated Operating Voltage (Ue)	230V~
Rated Frequency (Fn)	50/60Hz
Phase	1
Rated insulation voltage (Ui)	300V
Rated Impulse Withstand Voltage (Uimp)	4kV
Earthing System(s)	TN/TT
Manufacturing Material	Mild Steel
Useable Ways	8
Method of Mounting	Wall Mounting
Modular Ways	11
Impact Resistance (IK)	IK05
Ingress Protection Rating	IP2XC
Finish Colour	White RAL 9003

REGISTRY

Barcode	5026992000144
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Packaging Material	Cardboard
Min Order Quantity	1
Gross Weight (kg)	3.1 kg
Knockout Arrangement	ROUND K/O
Reference Standard(s)	BS EN 61439-3, BS EN60947-3, BS EN61643-11
Country of Origin	CN
Conformity Marks	UKCA
Pollution degree	2
WEEE Category	9