

## Consumer Unit 8way HI - 100A MS+T2SPD

- PRO Metal Consumer Unit Range, suitable for residential installations
- Fully interchangeable switched and un-switched neutral pole RCBO option
- Type 2 Surge Protection Device Pre-installed & wired
- The round knockouts range are designed for the installation of round cable glands, conduits, cable grommets, and for terminating SWA final circuit cables with complete flexibility.

# PRO-R08W-R1S

### TECHNICAL DATA

| | |
|---|---|
| Rated Operating Voltage (Ue) | 230V~ |
| Rated Frequency (Fn) | 50/60Hz |
| Phase | 1 |
| Rated insulation voltage (Ui) | 300V |
| Rated Impulse Withstand Voltage (Uimp) | 4kV |
| Earthing System(s) | TN-S, TN-C-S-(PME), TT |
| Manufacturing Material | Mild Steel |
| Useable Ways | 8 |
| Method of Mounting | Wall Mounting |
| Modular Ways | 11 |
| Impact Resistance (IK) | IK05 |
| Ingress Protection Rating | IP2XC |
| Finish Colour | White RAL 9003 |

### REGISTRY

| | |
|---|---|
| Barcode | 5026992000144 |
| Pkg. level 1 - Product Qty. | 1 |
| Pkg. level 1 - Dimensions (HWD) | 28 x 11.5 x 26 mm |
| Pkg. level 1 - Volume ($dm^3$) | 8.372 |
| Pkg. level 1 - Gross weight (kg) | 3.21 |
| Pkg. level 1 - Carton Weight (kg) | 0.193 |
| Pkg. level 1 - Packaging Material | Inner Corrugated Box |
| Pkg. level 2 - Dimensions (HWD) | 57 x 38 x 28.5 mm |
| Pkg. level 2 - Volume ($dm^3$) | 61.731 |
| Pkg. level 2 - Gross Weight (kg) | 20.08 |
| Pkg. level 2 - Carton Weight (kg) | 0.83 |

Lewden Ltd., Unit 4, Bradbury, Drive, Springwood Industrial Estate, Braintree, Essex, CM7

Tel +44 (0)1376 336200, www.lewden.com, Sales@lewden.co.uk