



Consumer Unit 14way HI - 100A MS+T2SPD

- PRO Metal Consumer Unit Range, suitable for residential installations
- Fully interchangeable switched and un-switched neutral pole RCBO option
- Type 2 Surge Protection Device Pre-installed & wired
- The round knockouts range are designed for the installation of round cable

PRO-R14W-R1S

TECHNICAL DATA

Rated Operating Voltage (Ue)	230V~
Rated Frequency (Fn)	50/60Hz
Phase	1
Rated insulation voltage (Ui)	300V
Rated Impulse Withstand Voltage (Uimp)	4kV
Earthing System(s)	TN/TT
Manufacturing Material	Mild Steel
Useable Ways	14
Method of Mounting	Wall Mounting
Modular Ways	17
Impact Resistance (IK)	IK05
Ingress Protection Rating	IP2XC
Finish Colour	White RAL 9003

REGISTRY

Barcode	5026992000175
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Packaging Material	Cardboard
Min Order Quantity	0
Gross Weight (kg)	4.027 kg
Knockout Arrangement	ROUND K/O
Reference Standard(s)	BS EN 61439-3, BS EN60947-3, BS EN61643-11
Country of Origin	CN
Conformity Marks	UKCA
Pollution degree	2
WEEE Category	9