

Consumer Unit 19way HI - 100A MS+T2SPD

- PRO Metal Consumer Unit Range, suitable for residential installations
- Fully interchangeable switched and un-switched neutral pole RCBO option
- Type 2 Surge Protection Device Pre-installed & wired
- The round knockouts range are designed for the installation of round cable glands, conduits, cable grommets, and for terminating SWA final circuit cables with complete flexibility.

PRO-R19W-R1S

TECHNICAL DATA

Rated Operating Voltage (Ue)	230V~
Rated Frequency (Fn)	50/60Hz
Phase	1
Rated insulation voltage (Ui)	300V
Rated Impulse Withstand Voltage (Uimp)	4kV
Earthing System(s)	TN-S, TN-C-S-(PME), TT
Manufacturing Material	Mild Steel
Useable Ways	19
Method of Mounting	Wall Mounting
Modular Ways	22
Impact Resistance (IK)	IK05
Ingress Protection Rating	IP2XC
Finish Colour	White RAL 9003

REGISTRY

Barcode	5026992000182
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Dimensions (HWD)	28 x 11.5 x 46 mm
Pkg. level 1 - Volume (dm^3)	14.812
Pkg. level 1 - Gross weight (kg)	5.01
Pkg. level 1 - Carton Weight (kg)	0.29
Pkg. level 1 - Packaging Material	Inner Corrugated Box
Pkg. level 2 - Dimensions (HWD)	48 x 30 x 48.5 mm
Pkg. level 2 - Volume (dm^3)	69.84
Pkg. level 2 - Gross Weight (kg)	20.83
Pkg. level 2 - Carton Weight (kg)	0.78

Lewden Ltd., Unit 4, Bradbury, Drive, Springwood Industrial Estate, Braintree, Essex, CM7

Tel +44 (0)1376 336200, www.lewden.com, Sales@lewden.co.uk