



RCBO B06A 30mA 1MOD 1P+N SWITCHED

- 6kA residual current circuit breaker with integral overcurrent protection.
- double pole switching for complete isolation in the event of a fault
- switch neutral pole significantly reduces the instalation and commissioning
- Class A residual current protection
- Single module RCBOs are suitable for use in TN & TT network systems

RCBO-B06/30/1PNA

TECHNICAL DATA

Rated Operating Voltage (Ue)	230-240V~
Rated Operational Current (Ie)	6A
Rated Residual Operating Current (I _{ΔN})	30mA
Rated Frequency (Fn)	50/60Hz
ICC Rating (kA)	6
Short circuit withstand current (1s)	6kA
Trip Curve	B
Type of RCBO	A
Phase	1
Energy Limiting Class	3
Rated Impulse Withstand Voltage (Uimp)	4kV

REGISTRY

Barcode	5026992045299
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Dimensions (HWD)	122x82x35 mm
Pkg. level 1 - Volume (dm ³)	0.350
Pkg. level 1 - Gross weight (kg)	0.180
Pkg. level 1 - Carton Weight (kg)	0.025
Pkg. level 1 - Packaging Material	Cardboard
Pkg. level 2 - Product Qty.	40
Pkg. level 2 - Dimensions (HWD)	382 x 280 x 180 mm
Pkg. level 2 - Volume (dm ³)	19.2
Pkg. level 2 - Gross Weight (kg)	7.6
Pkg. level 2 - Carton Weight	0.400