



Bidirectional RCBO B6A 6kA 30mA Type A

- 6kA residual current circuit breaker with integral overcurrent protection.
- double pole switching for complete isolation in the event of a fault
- switch neutral pole significantly reduces the installation and commissioning
- Bi-directional polarity
- Single module RCBOs are suitable for use in TN & TT network systems

RCBO-B06/30/1PNAB

TECHNICAL DATA

Rated Operating Voltage (Ue)	230-240V~
Rated Operational Current (Ie)	6A
Rated Residual Operating Current (I _{ΔN})	30mA
Rated Frequency (Fn)	50/60Hz
ICC Rating (kA)	6
Short circuit withstand current (1s)	6kA
Trip Curve	B
Type of RCBO	A
Phase	1
Energy Limiting Class	3
Rated Impulse Withstand Voltage (Uimp)	4kV

REGISTRY

Barcode	5026992000007
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Dimensions (HWD)	35x132x83 mm
Pkg. level 1 - Packaging Material	Cardboard
Pkg. level 2 - Packaging Material	Cardboard
Min Order Quantity	40
Gross Weight (kg)	0.201
Quantity Interval	12
Reference Standard(s)	IEC /BS EN61009-1
Country of Origin	CN
Conformity Marks	UKCA + CE
Pollution degree	2