



RCBO B6A 6kA 30mA Type A

- 6kA breaking capacity
- 30mA sensitivity
- Single pole + neutral
- Un-switched neutral
- 114mm height, 18mm width

RCBO-B06/30/SPA

TECHNICAL DATA

Rated Operating Voltage (Ue)	230-240V~
Rated Operational Current (Ie)	6A
Rated Residual Operating Current (I⊠N)	30mA
Rated Frequency (Fn)	50/60Hz
ICC Rating (kA)	6
Short circuit withstand current (1s)	6kA
Trip Curve	B
Type of RCBO	A
Phase	1
Energy Limiting Class	3
Rated Impulse Withstand Voltage (Uimp)	4kV

REGISTRY

Barcode	5026992046203
Pkg. level 1 - Product Qty.	1
Pkg. level 1 - Dimensions (HWD)	122x82x35 mm
Pkg. level 1 - Volume (dm^3)	0.350
Pkg. level 1 - Gross weight (kg)	0.180
Pkg. level 1 - Carton Weight (kg)	0.020
Pkg. level 1 - Packaging Material	Cardboard
Pkg. level 2 - Product Qty.	40
Pkg. level 2 - Dimensions (HWD)	382x280x180 mm
Pkg. level 2 - Volume (dm^3)	19.2
Pkg. level 2 - Gross Weight (kg)	7.5
Pkg. level 2 - Carton Weight	0.400

Lewden Ltd., Unit 4, Bradbury, Drive, Springwood Industrial Estate, Braintree, Essex, CM7

Tel +44 (0)1376 336200, www.lewden.com, Sales@lewden.co.uk