RCBO-B16/30/1HP

RCBO B16A Type A 30mA

Residual Current Circuit Breaker

Single module 6kA RCBO (RCBO-B16/30/1HP) for consumer units and distribution boards. 16A, B trip curve, 30mA sensitivity, Type B RCD. Protects against overloads, short circuits and earth leakage.

- 6kA breaking capacity
- 30mA sensitivity
- Detects DC fault currents
- High frequency operation (20kHz+)
- Ideal for heat pumps & EV charging

TECHNICAL DATA

Ingress Protection Rating	IP20	**Rated Operating Voltage (Ue)**	230-240V~
Phase	1	**Poles**	1P+swN
Product Dimensions (HWD)	118 x 18 x 76 mm	**Rated Operational Current (Ie)**	16A
Rated Residual Operating Current (IΔN)	30mA	**Terminal Tightening Torque**	Line 2.5Nm, Load 1.2Nm
Product Net Weight (kg)	0.17 kg	**Barcode**	5026992058336
WEEE Category	9	**Warranty**	2 Years

Lewden Ltd., Unit 4, Bradbury Drive, Springwood Industrial Estate, Braintree, Essex, CM7 2SD
Tel +44 (0) 1376 336200, www.lewden.com, Sales@lewden.co.uk