


Yaxley Slim Circular Tri-Colour IP65 20W Dimmable Emergency



Key Features

- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Maintained or non-maintained high output Emergency operation
- Selectable 3000K, 4000K or 5500K colour temperature
- IP65 rated housing
- Polycarbonate housing and diffuser
- Rear halo effect
- Hinged gear tray

Key Data

| | |
|--------------------|----------------------|
| Power | 20W |
| Luminous Flux | 1900lm/2000lm/1900lm |
| Colour Temperature | 3000K/4000K/5500K |
| IP Rating | IP65 |

| | |
|------------|---------------------------------|
| Dimensions | ø470 x 92mm |
| Warranty | 5 Years (Registration Required) |

Technical Specifications

| | |
|----------------------------|-------------------------|
| Colour Rendering | >80 CRI |
| Driver Output Voltage (DC) | 36-42V |
| Fire Rating | V2 |
| Input Voltage (AC) | 220-240V |
| Lamp Viewing Angle | 115° |
| LED Manufacturer | Jingrui |
| LED Type | SMD 2835 |
| Luminaire Efficacy | 100lm/W |
| Luminous Flux Factor | 15% |
| No. of LEDs | 156 |
| Operating Temp. | 0°C to +45°C |
| Power Factor | >0.9 |
| Recharge Period | 24H |
| Self Test | No |
| Total Circuit Power (W) | 20W +/- 1.5W |
| UGR Rating | More than 19 |
| Weight | 2.01Kg |
| Driver Manufacturer | Tridonic Premium Series |
| Electrical Class | 2 |
| Housing Colour | White |
| Housing Material | Polycarbonate |
| Lifespan LM80 | 50,000 Hours |
| Manufacturer | NET LED Lighting |
| Battery Pack | LiFePO4 |

| | |
|---------------------|---------------------------------------------------|
| Diffuser Material | Polycarbonate |
| Dimmable | Yes |
| Dimming Input Type | one4all Dimming - DALI 1 & 2 and switchDIM (Push) |
| Emergency Kit | 1 Year Warranty |
| Emergency Operation | >3H |
| Emergency Pack | Streamer |