


NEWTON WHITE POLYCARBONATE BULKHEAD 4000K IP65 16W MICROWAVE

NET-33-06-84



Features & Benefits

- Detection range from 2m to 10m
- Hold time from 5 seconds to 10 minutes
- Corridor function 0% or 10%
- IP65 and IK10 rated housing
- Rear or side entry
- Side conduit entry

Key Data

Power	16W
Luminous Flux	1300lm/1550lm/1400lm
Colour Temperature	4000K
IP Rating	IP65
IK Rating	IK10
Dimensions	Ø282 x 86.5mm
Warranty	3 Years

Compatible Accessories

NET-51-04-59	Photocell Kit for Outdoor Lighting
--------------	------------------------------------

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	90lm/W
LED Manufacturer	Honglitrronic
LED Type	SMD 2835
No. of LEDs	52
Driver Manufacturer	Merrytek
Driver Output Voltage (DC)	36-42V
Total Circuit Power (W)	16W +/- 1.5W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	115°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan LM80	35,000 Hours
UGR Rating	More than 19
Weight	1.04Kg
Manufacturer	NET LED Lighting
Fire Rating	V0
Max. Detection Distance	6m
Housing Colour	White
Housing Material	Polycarbonate
Diffuser Material	Polycarbonate
Max. Detection Area	6m
Sensor Manufacturer	Merrytek
Sensor IP Rating	IP20
Standby Dimming Level	0% / 10%
Corridor Function	Yes

Other Options



Description	
NET-33-06-80	Newton White Polycarbonate Bulkhead 4000K IP65 16W Standard
NET-33-06-88	Newton White Polycarbonate Bulkhead 4000K IP65 16W Emergency
NET-33-06-84	Newton White Polycarbonate Bulkhead 4000K IP65 16W Microwave Sensor
NET-33-06-86	Newton White Polycarbonate Bulkhead 4000K IP65 16W Microwave Sensor Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

3K

4K

5.5K

INTEGRAL MICROWAVE SENSOR

Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent the diffuser shattering into small, indistinct pieces

LITHIUM ION BATTERY

Requires little maintenance and has a long lifespan

Emergency options only

DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

Photocell options only

REAR OR SIDE CABLE ENTRY

Protect your wiring from harsh weather and possible tampering

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

IP65 RATED HOUSING

Protect your bulkhead from water and dust