



## KINGSTON PANEL UGR<19 TRI-COLOUR 1200X300 27W TP(A) EMERGENCY

NET-39-03-12



### Features & Benefits

- Emergency function
- Low glare diffuser with UGR rating <19
- TP(a) flammability-rated diffuser
- PMMA Light Guide path for even light distribution
- Selectable 3000K, 4000K or 5500K colour temperature
- Flicker-free driver

### Key Data

<b>Power</b>	27W
<b>Luminous Flux</b>	3000lm/3300lm/3200lm
<b>Colour Temperature</b>	3000K/4000K/5500K
<b>IP Rating</b>	IP40 Front/IP20 Rear
<b>Dimensions</b>	1195 x 295 x 10mm
<b>Warranty</b>	5 Years (Registration Required)

### Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-60-16-20	Tridonic Bluetooth Dimmable Driver 800mA (600x600mm and 1200x300mm Panels)
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-03-45	Panel Suspension Rails for 1200mm Panels
NET-39-03-41	Panel Surface Box 1200x300mm

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.95
Luminaire Efficacy	122lm/W
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	240
Driver Manufacturer	Tridonic Advanced Series
Driver Output Voltage (DC)	33-42V
Total Circuit Power (W)	27W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	2.95Kg
Manufacturer	Lumlux Corp.
Frame Colour	White
Hours Maintained	3H
Luminous Flux Factor	10%
Self Test	No
Battery Pack	LiFePO4
Emergency Kit	3 Year Warranty
Emergency Operation	>3H



## Other Options

Description	
NET-39-03-06	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Standard
NET-39-03-12	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Emergency
NET-39-03-13	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Dimmable one4all
NET-39-03-14	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Dimmable Emergency
NET-39-03-60	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Self Test Emergency
NET-39-03-61	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Dimmable Self Test Emergency
NET-39-03-62	Kingston Panel UGR<19 Tri-Colour 1200x300 27W TP(a) Dimmable DALI Emergency

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)

3K

4K

5.5K


## SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature  
3000K, 4000K or 5500K

## 3H EMERGENCY OPERATION

Ensures the fitting comes on in  
the event of a power failure

*Emergency options only*



## LOW GLARE UGR<19 AND TP(A) FLAMMABILITY RATED DIFFUSER

Reduce headaches and comply  
with Building Regulations

## PMMA LIGHT GUIDE PLATE

Creates a uniform light  
distribution and extend  
the lifespan

## EDGELIT DESIGN

Allows the fitting to have a sleek and  
slim profile, making them suitable for  
applications where space is limited