



KINGSTON PANEL UGR<19 TRI-COLOUR 1200X600 50W TP(A) EMERGENCY

NET-39-03-15



Features & Benefits

- Emergency function
- Low glare diffuser with UGR rating <19
- TP(a) flammability-rated diffuser
- PMMA Light Guide path for even light distribution
- Selectable 3000K, 4000K or 5500K colour temperature
- Flicker-free driver

Key Data

Power	50W
Luminous Flux	4800lm/5500lm/5200lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP40 Front/IP20 Rear
Dimensions	1195 x 595 x 10mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-60-16-30	Tridonic Bluetooth Dimmable Driver 1200mA (1200x600mm Panels)
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-03-45	Panel Suspension Rails for 1200mm Panels
NET-39-03-43	Panel Surface Box 1200x600mm

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.95
Luminaire Efficacy	110lm/W
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	456
Driver Manufacturer	Tridonic Advanced Series
Driver Output Voltage (DC)	31-43V
Total Circuit Power (W)	50W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	5.4Kg
Manufacturer	Lumlux Corp.
Frame Colour	White
Hours Maintained	3H
Luminous Flux Factor	6%
Self Test	No
Battery Pack	LiFePO4
Emergency Kit	3 Year Warranty
Emergency Operation	>3H



Other Options

Description	
NET-39-03-08	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Standard
NET-39-03-15	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Emergency
NET-39-03-16	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Dimmable one4all
NET-39-03-17	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Dimmable Emergency
NET-39-03-63	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Self Test Emergency
NET-39-03-64	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Dimmable Self Test Emergency
NET-39-03-66	Kingston Panel UGR<19 Tri-Colour 1200x600 50W TP(a) Dimmable DALI Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

3K

4K

5.5K


SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

3H EMERGENCY OPERATION

Ensures the fitting comes on in the event of a power failure

Emergency options only



LOW GLARE UGR<19 AND TP(A) FLAMMABILITY RATED DIFFUSER

Reduce headaches and comply with Building Regulations

PMMA LIGHT GUIDE PLATE

Creates a uniform light distribution and extend the lifespan

EDGELIT DESIGN

Allows the fitting to have a sleek and slim profile, making them suitable for applications where space is limited