


## KINGSTON PANEL UGR<19 TRI-COLOUR 300X300 10W TP(A) DIMMABLE EMERGENCY

NET-39-03-36



### Key Data

Power	10W
Luminous Flux	950lm/1080lm/1000lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP40 Front/IP20 Rear
Dimensions	295 x 295 x 10mm
Warranty	5 Years (Registration Required)

### Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-16-03	Burgess Z Clips for Kingston Panels

#### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)




**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	200-240V
Power Factor	>0.95
Luminaire Efficacy	108lm/W
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	120
Driver Manufacturer	Tridonic Excite Series
Driver Output Voltage (DC)	30-42V
Total Circuit Power (W)	10W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	0.715Kg
Manufacturer	Lumlux Corp.
Frame Colour	White
Hours Maintained	3H
Luminous Flux Factor	30%
Self Test	No
Battery Pack	LiFePO4
Dimming Input Type	Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
Emergency Kit	3 Year Warranty

## Other Options

Description	
NET-39-03-00	Streamer Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Standard
NET-39-03-32	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Emergency
NET-39-03-34	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Self Test Emergency
NET-39-03-35	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable one4all
NET-39-03-36	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable Emergency
NET-39-03-37	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable Self Test Emergency
NET-39-03-38	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable DALI Emergency



## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

## WIRELESS CONTROL

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

*Bluetooth options only*

## TRIDONIC DIMMABLE DRIVER

Customise lighting levels and reduce electricity consumption

*Dimmable options only*

## 3H EMERGENCY OPERATION

Ensures the fitting comes on in the event of a power failure

*Emergency options only*



3K

4K

5.5K

## SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

## LOW GLARE UGR<19 AND TP(A) FLAMMABILITY RATED DIFFUSER

Reduce headaches and comply with Building Regulations

## EDGE LIT DESIGN

Allows the fitting to have a sleek and slim profile, making them suitable for applications where space is limited