


KINGSTON PANEL UGR<19 TRI-COLOUR 500X500 16W TP(A) SELF TEST EMERGENCY

NET-39-03-50



Key Data

Power	16W
Luminous Flux	1800lm/2100lm/1900lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP40 Front/IP20 Rear
Dimensions	495 x 495 x 10mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-16-03	Burgess Z Clips for Kingston Panels

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.95
Luminaire Efficacy	131lm/W
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	192
Driver Manufacturer	Tridonic Advanced Series
Driver Output Voltage (DC)	33-42V
Total Circuit Power (W)	16W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	2.25Kg
Manufacturer	Lumlux Corp.
Frame Colour	White
Hours Maintained	3H
Self Test	Yes
Battery Pack	LiFePO4
Emergency Kit	3 Year Warranty
Emergency Operation	>3H
Emergency Pack	Fox Lux

Other Options

Description	
NET-39-03-50	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Self Test Emergency
NET-39-03-51	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Dimmable Self Test Emergency
NET-39-03-52	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Dimmable DALI Emergency
NET-39-03-02	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Standard
NET-39-03-03	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Emergency
NET-39-03-05	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Dimmable one4all
NET-39-03-07	Kingston Panel UGR<19 Tri-Colour 500x500 16W TP(a) Dimmable Emergency



All units are in mm

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

3K

4K

5.5K


SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature
3000K, 4000K or 5500K

3H EMERGENCY OPERATION

Ensures the fitting comes on in
the event of a power failure

Emergency options only



LOW GLARE UGR<19 AND TP(A) FLAMMABILITY RATED DIFFUSER

Reduce headaches and comply
with Building Regulations

PMMA LIGHT GUIDE PLATE

Creates a uniform light
distribution and extend
the lifespan

EDGELIT DESIGN

Allows the fitting to have a sleek and
slim profile, making them suitable for
applications where space is limited