


KINGSTON PANEL UGR<19 TRI-COLOUR 600X600 27W TP(A) SELF TEST EMERGENCY

NET-39-03-53



Features & Benefits

- Self Test Emergency function
- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Low glare diffuser with UGR rating <19
- TP(a) flammability-rated diffuser
- PMMA Light Guide path for even light distribution
- Selectable 3000K, 4000K or 5500K colour temperature

Key Data

Power	27W
Luminous Flux	2900lm/3300lm/3000lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP40 Front/IP20 Rear
Dimensions	595 x 595 x 10mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-03-47	Panel Recessed Frame 600x600mm
NET-39-03-39	Panel Surface Box 600x600mm
NET-39-16-03	Burgess Z Clips for Kingston Panels
NET-39-16-05	Burgess Adjustable Z Clips for Kingston Panels

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.95
Luminaire Efficacy	122lm/W
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	240
Driver Manufacturer	Tridonic Advanced Series
Driver Output Voltage (DC)	33-42V
Total Circuit Power (W)	27W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	2.9Kg
Manufacturer	Lumlux Corp.
Frame Colour	White
Hours Maintained	3H
Luminous Flux Factor	10%
Self Test	Yes
Battery Pack	LiFePO4
Emergency Kit	3 Year Warranty
Emergency Operation	>3H
Emergency Pack	Foxlux

Other Options



Description	
NET-39-03-04	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Standard
NET-39-03-09	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Emergency
NET-39-03-10	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Dimmable one4all
NET-39-03-11	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Dimmable Emergency
NET-39-03-53	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Self Test Emergency
NET-39-03-54	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Dimmable Self Test Emergency
NET-39-03-55	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Dimmable DALI Emergency
NET-39-03-56	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Bluetooth
NET-39-03-57	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Bluetooth Emergency
NET-39-03-58	Kingston Panel UGR<19 Tri-Colour 600x600 27W TP(a) Bluetooth Self Test Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

3K

4K

5.5K


SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature
3000K, 4000K or 5500K

3H EMERGENCY OPERATION

Ensures the fitting comes on in
the event of a power failure

Emergency options only



LOW GLARE UGR<19 AND TP(A) FLAMMABILITY RATED DIFFUSER

Reduce headaches and comply
with Building Regulations

PMMA LIGHT GUIDE PLATE

Creates a uniform light
distribution and extend
the lifespan

EDGELIT DESIGN

Allows the fitting to have a sleek and
slim profile, making them suitable for
applications where space is limited