



FOXTON BATTEN TRI-COLOUR 1200MM (4FT) 20W DIMMABLE ONE4ALL

NET-41-11-08



Features & Benefits

- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Selectable colour temperature 3000K, 4000K or 5700K
- Rear or end cable entry
- Tridonic driver as standard
- Push connector for quick and easy installation
- Diffuser comes with built-in LEDs

Key Data

Power	20W
Luminous Flux	2600lm
Colour Temperature	3000K/4000K/5700K
IP Rating	IP20
IK Rating	IK04
Dimensions	1220 x 63 x 73mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-61-33-04	DALI Emergency Kit 3W/6W
NET-42-43-38	Merrytek Microwave Sensor IP65 20mm Knock Out
NET-46-16-04	Universal LED NCF / Batten Suspension Kit
NET-42-43-24	DALI Dimmer Switch
NET-51-11-01	PIR Sensor (External) for Battens and NCFs
NET-51-11-03	On/Off Step Dimming Sensor (External) for Battens and NCFs

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.90
Luminaire Efficacy	130lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	216
Driver Manufacturer	Tridonic Premium Series
Driver Output Voltage (DC)	20-54V
Total Circuit Power (W)	20W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	-10°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	1.400Kg
Manufacturer	Senselight
Fire Rating	V2
Housing Colour	White
Housing Material	Steel
Diffuser Material	Polycarbonate
Dimming Input Type	Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)

PRODUCT DIMENSIONS			
			
Size (ft)	A	B	C
2	600	63	73
4	1200	63	73
5	1500	63	73
6	1800	63	73

All units are in mm

Other Options

Description	
NET-41-11-91	Foxton Batten Tri-Colour 1200mm (4ft) 20W Standard
NET-41-11-92	Foxton Batten Tri-Colour 1200mm (4ft) 20W Emergency
NET-41-12-92	Foxton Batten Tri-Colour 1200mm (4ft) 20W Self Test Emergency
NET-41-11-08	Foxton Batten Tri-Colour 1200mm (4ft) 20W Dimmable one4all
NET-41-11-09	Foxton Batten Tri-Colour 1200mm (4ft) 20W Dimmable Emergency
NET-41-11-72	Foxton Batten Tri-Colour 1200mm (4ft) 20W Dimmable DALI Emergency
NET-41-11-73	Foxton Batten Tri-Colour 1200mm (4ft) 20W PIR Sensor On/Off
NET-41-11-74	Foxton Batten Tri-Colour 1200mm (4ft) 20W PIR Sensor On/Off Emergency
NET-41-11-75	Foxton Batten Tri-Colour 1200mm (4ft) 20W Microwave Sensor On/Off
NET-41-11-76	Foxton Batten Tri-Colour 1200mm (4ft) 20W Microwave Sensor On/Off Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

130
lm/W



**FLICKER-FREE
TRIDONIC
DIMMABLE DRIVER**

Ensure reliability, durability and performance leading to long-lasting LEDs

Dimmable options only

**COMBINED DIFFUSER
AND LEDS**

Stop juggling multiple parts and install a diffuser that comes with built-in LEDs

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

**REAR OR END
CABLE ENTRY**

Create seamless end-to-end lighting designs

WIRELESS CONTROL

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

Bluetooth options only



**SELECTABLE COLOUR
TEMPERATURE**

Choose your colour temperature 3000K, 4000K or 5700K