

## TRINITY SURFACE LINEAR TRI-COLOUR 1200MM (4FT) 32W DIMMABLE EMERGENCY


NET-41-11-38



DIM  
EMG


### Tridonic one4all Dimming Driver

Allows for DALI 1 & 2 and switchDIM (Push) dimming



### 3 Hour Emergency operation

The integral Emergency Battery ensures the fitting stays on in the event of an emergency or power failure



## Features & Benefits

- 3H Emergency operation
- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

## Key Data

<b>Power</b>	32W
<b>Luminous Flux</b>	4560lm
<b>Colour Temperature</b>	3000K/4000K/5700K
<b>IP Rating</b>	IP20
<b>Dimensions</b>	1200 x 170 x 79mm
<b>Warranty</b>	5 Years (Registration Required)

## Compatible Accessories

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

### NET LED Lighting

Buckingway Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)




**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	142lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	480
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	60V
Total Circuit Power (W)	32W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	2.280Kg
Manufacturer	Senselite Optoelectronic Technology Co. Ltd
Fire Rating	V2
Luminous Flux Factor	17%/12.5%
Self Test	No
Housing Colour	White
Housing Material	Steel
Battery Pack	LiFePO4
Diffuser Material	Polycarbonate
Dimming Input Type	one4all Dimming - DALI 1 & 2 and switchDIM
Emergency Kit	3 Year Warranty
Emergency Operation	>3H

Other Options



Description	
NET-41-11-30	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Standard
NET-41-11-32	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Emergency
NET-41-11-34	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Self Test Emergency
NET-41-11-36	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable one4all
NET-41-11-38	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable Emergency
NET-41-11-31	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable Self Test Emergency
NET-41-11-33	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable DALI Emergency
NET-41-11-35	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Sensor
NET-41-11-37	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Sensor Emergency
NET-41-11-39	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Self Test Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM  
FOR NEXT DAY DELIVERY

SELECTABLE COLOUR  
TEMPERATURE

Choose your colour  
temperature at the time of  
installation 3000K, 4000K  
or 5700K



TRIDONIC PREMIUM  
DIMMABLE DRIVER

Customise lighting levels  
and reduce electricity  
consumption

Dimmable options only

PUSH  
CONNECTOR

Reduce installation time  
with easy-to-use push  
fit terminals

REAR OR END  
CABLE ENTRY

Create seamless  
end-to-end lighting designs

WIRELESS CONTROL

Control the panel remotely via  
smartphone or tablet with it's  
Bluetooth Dimmable Driver

Bluetooth options only