

TRINITY SURFACE LINEAR TRI-COLOUR 1200MM (4FT) 23W/32W MICROWAVE SELF

NET-41-11-39



**Integral Microwave Sensor**

Save money and energy by ensuring the fitting only comes on when movement is detected

**Self Test Emergency operation**

Save time and money with a fitting that carries out its own testing in line with relevant standards

**Features & Benefits**

- Self Test Emergency function
- Integral Microwave Sensor
- Selectable power setting (23W or 32W) at the time of installation
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

**Key Data**

<b>Power</b>	23W/32W
<b>Luminous Flux</b>	3300lm/4560lm
<b>Colour Temperature</b>	3000K/4000K/5700K
<b>IP Rating</b>	IP20
<b>Dimensions</b>	1200 x 170 x 79mm
<b>Warranty</b>	5 Years (Registration Required)

**Compatible Accessories**

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

**NET LED Lighting**

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

<b>Input Voltage (AC)</b>	220-240V
<b>Power Factor</b>	>0.9
<b>Luminaire Efficacy</b>	142lm/W
<b>LED Manufacturer</b>	Jingrui
<b>LED Type</b>	SMD 2835
<b>No. of LEDs</b>	480
<b>Driver Manufacturer</b>	Tridonic
<b>Driver Output Voltage (DC)</b>	60V
<b>Total Circuit Power (W)</b>	23W/32W
<b>Electrical Class</b>	1
<b>Colour Rendering</b>	>80 CRI
<b>Lamp Viewing Angle</b>	120°
<b>Dimmable</b>	No
<b>Flicker-Free</b>	Yes
<b>Operating Temp.</b>	0°C to +40°C
<b>Lifespan LM80</b>	50,000 Hours
<b>UGR Rating</b>	More than 22
<b>Weight</b>	2.280Kg
<b>Manufacturer</b>	Senselite Optoelectronic Technology Co. Ltd
<b>Fire Rating</b>	V2
<b>Lux Levels</b>	2lux - 50lux or Disabled
<b>Max. Detection Distance</b>	6m
<b>Self Test</b>	Yes
<b>Housing Colour</b>	White
<b>Housing Material</b>	Steel
<b>Battery Pack</b>	LiFePO4
<b>Detection Angle</b>	150°(wall mt) / 360°(ceiling mt)
<b>Diffuser Material</b>	Polycarbonate
<b>Duration</b>	5s - 30min



## Other Options


	Description
NET-41-11-30	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Standard
NET-41-11-32	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Emergency
NET-41-11-34	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Self Test Emergency
NET-41-11-35	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable one4all
NET-41-11-38	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable Emergency
NET-41-11-31	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable Self Test Emergency
NET-41-11-33	Trinity Surface Linear Tri-Colour 1200mm (4ft) 32W Dimmable DALI Emergency
NET-41-11-35	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Sensor
NET-41-11-37	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Sensor Emergency
NET-41-11-39	Trinity Surface Linear Tri-Colour 1200mm (4ft) 23W/32W Microwave Self Test Emergency

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY



**SELECTABLE COLOUR TEMPERATURE**

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



**DUAL WATTAGE TRIDONIC DRIVER**

Choose the power setting at the time of installation

**INTEGRAL MICROWAVE SENSOR WITH 6M DETECTION DISTANCE AND 5S-30MIN HOLD TIME**

Save energy costs with a fitting that only lights the room when movement is detected

*Microwave Sensor options only*

**3H EMERGENCY OPERATION**

Ensures the fitting comes on in the event of a power failure

*Emergency options only*

**PUSH CONNECTOR**

Reduce installation time with easy-to-use push fit terminals

**REAR OR END CABLE ENTRY**

Create seamless end-to-end lighting designs