



## TRINITY SURFACE LINEAR TRI-COLOUR 1500MM (5FT) 50W BLUETOOTH

NET-41-11-41



### Features & Benefits

- Pre-set scenes and brightness levels
- Controlled via App or optional Bluetooth Dimmable/Scene Switch
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

### Key Data

|                           |                                 |
|---------------------------|---------------------------------|
| <b>Power</b>              | 50W                             |
| <b>Luminous Flux</b>      | 7120lm                          |
| <b>Colour Temperature</b> | 3000K/4000K/5700K               |
| <b>IP Rating</b>          | IP20                            |
| <b>Dimensions</b>         | 1500 x 170 x 79mm               |
| <b>Warranty</b>           | 5 Years (Registration Required) |

### Compatible Accessories

|              |                                  |
|--------------|----------------------------------|
| NET-51-11-02 | Cambridge/Trinity Suspension Kit |
|--------------|----------------------------------|

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

|                            |   |
|----------------------------|---|
| Input Voltage (AC)         | 220-240V                                    |
| Power Factor               | >0.9  |
| Luminaire Efficacy         | 142lm/W                                     |
| LED Manufacturer           | Jingrui                                     |
| LED Type                   | SMD 2835                                    |
| No. of LEDs                | 640   |
| Driver Manufacturer        | Tridonic                                    |
| Driver Output Voltage (DC) | 60V   |
| Total Circuit Power (W)    | 50W   |
| Electrical Class           | 1   |
| Colour Rendering           | >80 CRI                                     |
| Lamp Viewing Angle         | 120°  |
| Dimmable                   | Yes   |
| Flicker-Free               | Yes   |
| Operating Temp.            | 0°C to +40°C                                |
| Lifespan LM80              | 50,000 Hours                                |
| UGR Rating                 | More than 22                                |
| Weight                     | 2.890Kg                                     |
| Manufacturer               | Senselite Optoelectronic Technology Co. Ltd |
| Fire Rating                | V2  |
| Housing Colour             | White                                       |
| Housing Material           | Steel                                       |
| Diffuser Material          | Polycarbonate                               |
| Dimming Input Type         | Bluetooth Dimmable                          |



## Other Options

| Description  |   |
|--------------|---|
| NET-41-11-40 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Standard                             |
| NET-41-11-42 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Emergency                            |
| NET-41-11-44 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Self Test Emergency                  |
| NET-41-11-46 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable one4all                         |
| NET-41-11-48 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable Emergency                       |
| NET-41-12-48 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable Self Test Emergency             |
| NET-41-11-43 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable DALI Emergency                  |
| NET-41-11-45 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor                     |
| NET-41-11-47 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor Emergency           |
| NET-41-11-49 | Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor Self Test Emergency |

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)

**SELECTABLE COLOUR TEMPERATURE**

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



**TRIDONIC PREMIUM DIMMABLE DRIVER**

Customise lighting levels and reduce electricity consumption

*Dimmable options only*

**PUSH CONNECTOR**

Reduce installation time with easy-to-use push fit terminals

**REAR OR END CABLE ENTRY**

Create seamless end-to-end lighting designs

**WIRELESS CONTROL**

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

*Bluetooth options only*