

TRINITY SURFACE LINEAR TRI-COLOUR 1800MM (6FT) 60W DIMMABLE SELF TEST


NET-41-11-51



DIM
SELF


Tridonic one4all Dimming Driver

Allows for DALI 1 & 2 and switchDIM (Push) dimming



Self Test Emergency operation

Save time and money with a fitting that carries out its own testing in line with relevant standards



Features & Benefits

- Self Test Emergency function
- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

Key Data

Power	60W
Luminous Flux	8625lm
Colour Temperature	3000K/4000K/5700K
IP Rating	IP20
Dimensions	1800 x 170 x 79mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	143lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	760
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	60V
Total Circuit Power (W)	60W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	3.510Kg
Manufacturer	Senselite Optoelectronic Technology Co. Ltd
Fire Rating	V2
Luminous Flux Factor	8%
Self Test	Yes
Housing Colour	White
Housing Material	Steel
Battery Pack	LiFePO4
Diffuser Material	Polycarbonate
Dimming Input Type	one4all Dimming - DALI 1 & 2 and switchDIM
Emergency Kit	3 Year Warranty
Emergency Operation	>3H



Other Options

Description	
NET-41-11-50	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Standard
NET-41-11-52	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Emergency
NET-41-11-54	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Self Test Emergency
NET-41-11-56	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable one4all
NET-41-11-58	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Emergency
NET-41-11-51	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Self Test Emergency
NET-41-11-53	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable DALI Emergency
NET-41-11-55	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor
NET-41-11-57	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Emergency
NET-41-11-59	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Self Test Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



TRIDONIC PREMIUM DIMMABLE DRIVER

Customise lighting levels and reduce electricity consumption

Dimmable options only

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

REAR OR END CABLE ENTRY

Create seamless end-to-end lighting designs

WIRELESS CONTROL

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

Bluetooth options only