


## TRINITY SURFACE LINEAR TRI-COLOUR 1800MM (6FT) 41W/60W SELF TEST

NET-41-11-54



### Features & Benefits

- Self Test Emergency function
- Selectable power setting (41W or 60W) at the time of installation
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

### Key Data

|                           |                                 |
|---------------------------|---------------------------------|
| <b>Power</b>              | 41W/60W                         |
| <b>Luminous Flux</b>      | 5760lm/8625lm                   |
| <b>Colour Temperature</b> | 3000K/4000K/5700K               |
| <b>IP Rating</b>          | IP20                            |
| <b>Dimensions</b>         | 1800 x 170 x 79mm               |
| <b>Warranty</b>           | 5 Years (Registration Required) |

### Compatible Accessories

|              |                                  |
|--------------|----------------------------------|
| NET-51-11-02 | Cambridge/Trinity Suspension Kit |
|--------------|----------------------------------|

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)




**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

Technical Specifications

|                            |   |
|----------------------------|---|
| Input Voltage (AC)         | 220-240V                                    |
| Power Factor               | >0.9  |
| Luminaire Efficacy         | 143lm/W                                     |
| LED Manufacturer           | Jingrui                                     |
| LED Type                   | SMD 2835                                    |
| No. of LEDs                | 760   |
| Driver Manufacturer        | Tridonic                                    |
| Driver Output Voltage (DC) | 60V   |
| Total Circuit Power (W)    | 41W/60W                                     |
| Electrical Class           | 1   |
| Colour Rendering           | >80 CRI                                     |
| Lamp Viewing Angle         | 120°  |
| Dimmable                   | No  |
| Flicker-Free               | Yes   |
| Operating Temp.            | 0°C to +40°C                                |
| Lifespan LM80              | 50,000 Hours                                |
| UGR Rating                 | More than 22                                |
| Weight                     | 3.510Kg                                     |
| Manufacturer               | Senselite Optoelectronic Technology Co. Ltd |
| Fire Rating                | V2  |
| Luminous Flux Factor       | 9.75%/6.6%                                  |
| Self Test                  | Yes   |
| Housing Colour             | White                                       |
| Housing Material           | Steel                                       |
| Battery Pack               | LiFePO4                                     |
| Diffuser Material          | Polycarbonate                               |
| Emergency Kit              | 3 Year Warranty                             |
| Emergency Operation        | >3H   |
| Emergency Pack             | Streamer                                    |

Other Options



| Description  |   |
|--------------|---|
| NET-41-11-50 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Standard                             |
| NET-41-11-52 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Emergency                            |
| NET-41-11-54 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Self Test Emergency                  |
| NET-41-11-56 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable one4all                         |
| NET-41-11-58 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Emergency                       |
| NET-41-11-51 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Self Test Emergency             |
| NET-41-11-53 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable DALI Emergency                  |
| NET-41-11-55 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor                     |
| NET-41-11-57 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Emergency           |
| NET-41-11-59 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Self Test Emergency |

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM  
FOR NEXT DAY DELIVERY

**SELECTABLE COLOUR TEMPERATURE**

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



**DUAL WATTAGE TRIDONIC DRIVER**

Choose the power setting at the time of installation

**INTEGRAL MICROWAVE SENSOR WITH 6M DETECTION DISTANCE AND 5S-30MIN HOLD TIME**

Save energy costs with a fitting that only lights the room when movement is detected

**3H EMERGENCY OPERATION**

Ensures the fitting comes on in the event of a power failure

*Emergency options only*

**PUSH CONNECTOR**

Reduce installation time with easy-to-use push fit terminals

**REAR OR END CABLE ENTRY**

Create seamless end-to-end lighting designs

*Microwave Sensor options only*