



## FOXTON BATTEN TRI-COLOUR 1500MM (5FT) 50W BLUETOOTH

NET-41-11-84



### Features & Benefits

- Pre-set scenes and brightness levels
- Controlled via the App or optional Bluetooth Dimmable/Scene Switch
- Selectable colour temperature 3000K, 4000K or 5700K
- Rear or end cable entry
- Tridonic driver as standard
- Push connector for quick and easy installation

### Key Data

<b>Power</b>	50W
<b>Luminous Flux</b>	6500lm
<b>Colour Temperature</b>	3000K/4000K/5700K
<b>IP Rating</b>	IP20
<b>IK Rating</b>	IK04
<b>Dimensions</b>	1520 x 63 x 73mm
<b>Warranty</b>	5 Years (Registration Required)

### Compatible Accessories

NET-61-33-04	DALI Emergency Kit 3W/6W
NET-42-43-38	Merrytek Microwave Sensor IP65 20mm Knock Out
NET-46-16-04	Universal LED NCF / Batten Suspension Kit
NET-60-16-80	Tridonic Bluetooth Multifunction Dimmable/Scene Switch
NET-42-43-24	DALI Dimmer Switch
NET-51-11-01	PIR Sensor (External) for Battens and NCFs

### NET LED Lighting

Buckingway Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.90
Luminaire Efficacy	130lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	480
Driver Manufacturer	Tridonic Premium Series
Driver Output Voltage (DC)	20-54V
Total Circuit Power (W)	50W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	-10°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Manufacturer	Senselight
Fire Rating	V2
Housing Colour	White
Housing Material	Steel
Diffuser Material	Polycarbonate
Dimming Input Type	Bluetooth Dimming

PRODUCT DIMENSIONS			
			
Size (ft)	A	B	C
2	600	63	73
4	1200	63	73
5	1500	63	73
6	1800	63	73

All units are in mm

## Other Options

Description	
NET-41-11-96	Foxton Batten Tri-Colour 1500mm (5ft) 50W Standard
NET-41-11-95	Foxton Batten Tri-Colour 1500mm (5ft) 50W Emergency
NET-41-12-95	Foxton Batten Tri-Colour 1500mm (5ft) 50W Self Test Emergency
NET-41-11-13	Foxton Batten Tri-Colour 1500mm (5ft) 50W Dimmable one4all
NET-41-11-14	Foxton Batten Tri-Colour 1500mm (5ft) 50W Dimmable Emergency
NET-41-11-82	Foxton Batten Tri-Colour 1500mm (5ft) 50W Dimmable DALI Emergency
NET-41-11-83	Foxton Batten Tri-Colour 1500mm (5ft) 50W PIR Sensor On/Off
NET-41-12-83	Foxton Batten Tri-Colour 1500mm (5ft) 50W PIR Sensor On/Off Emergency
NET-41-11-84	Foxton Batten Tri-Colour 1500mm (5ft) 50W Bluetooth
NET-41-12-84	Foxton Batten Tri-Colour 1500mm (5ft) 50W Bluetooth Emergency

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)

130  
lm/W



**FLICKER-FREE  
TRIDONIC  
DIMMABLE DRIVER**

Ensure reliability, durability and performance leading to long-lasting LEDs

*Dimmable options only*

**COMBINED DIFFUSER  
AND LEDS**

Stop juggling multiple parts and install a diffuser that comes with built-in LEDs

**PUSH CONNECTOR**

Reduce installation time with easy-to-use push fit terminals

**REAR OR END  
CABLE ENTRY**

Create seamless end-to-end lighting designs

**WIRELESS CONTROL**

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

*Bluetooth options only*



**SELECTABLE COLOUR  
TEMPERATURE**

Choose your colour temperature 3000K, 4000K or 5700K