

## TRINITY SURFACE LINEAR TRI-COLOUR 1500MM (5FT) 50W BLUETOOTH

NET-41-12-41




### Optional Dimmable/Scene Switch

Compatible with any of our Bluetooth Dimmable Drivers and gives you ultimate multi-room scene control



### 3 Hour Emergency operation

The integral Emergency Battery ensures the fitting stays on in the event of an emergency or power failure



## Features & Benefits

- 3H Emergency function
- Pre-set scenes and brightness levels
- Controlled via App or optional Bluetooth Dimmable/Scene Switch
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

## Key Data

<b>Power</b>	50W
<b>Luminous Flux</b>	7120lm
<b>Colour Temperature</b>	3000K/4000K/5700K
<b>IP Rating</b>	IP20
<b>Dimensions</b>	1500 x 170 x 79mm
<b>Warranty</b>	5 Years (Registration Required)

## Compatible Accessories

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	142lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	640
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	60V
Total Circuit Power (W)	50W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	2.890Kg
Manufacturer	Senselite Optoelectronic Technology Co. Ltd
Fire Rating	V2
Self Test	No
Housing Colour	White
Housing Material	Steel
Battery Pack	LiFePO4
Diffuser Material	Polycarbonate
Dimming Input Type	Bluetooth Dimmable



## Other Options

Description	
NET-41-11-40	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Standard
NET-41-11-42	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Emergency
NET-41-11-44	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Self Test Emergency
NET-41-11-46	Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable one4all
NET-41-11-48	Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable Emergency
NET-41-12-48	Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable Self Test Emergency
NET-41-11-43	Trinity Surface Linear Tri-Colour 1500mm (5ft) 50W Dimmable DALI Emergency
NET-41-11-45	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor
NET-41-11-47	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor Emergency
NET-41-11-49	Trinity Surface Linear Tri-Colour 1500mm (5ft) 34W/50W Microwave Sensor Self Test Emergency

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)

SELECTABLE COLOUR  
TEMPERATURE

Choose your colour  
temperature at the time of  
installation 3000K, 4000K  
or 5700K



TRIDONIC PREMIUM  
DIMMABLE DRIVER

Customise lighting levels  
and reduce electricity  
consumption

Dimmable options only

PUSH  
CONNECTOR

Reduce installation time  
with easy-to-use push  
fit terminals

REAR OR END  
CABLE ENTRY

Create seamless  
end-to-end lighting designs

WIRELESS CONTROL

Control the panel remotely via  
smartphone or tablet with it's  
Bluetooth Dimmable Driver

Bluetooth options only