


HILTON NCF 5500K 1200MM (4FT) 32W/40W STANDARD

NET-43-11-03


Features & Benefits

- 1-10V Dimming
- Dual Wattage driver allows a choice between 32W or 40W
- IP65 rated housing
- Tamper-proof stainless steel clips
- Easy-mounting clips
- High lumens per watt

Key Data

Power	32W/40W
Luminous Flux	4185lm/5160lm
Colour Temperature	5500K
IP Rating	IP65
IK Rating	IK08
Dimensions	1200 x 125 x 88mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-42-43-33	Merrytek Microwave Sensor IP65 with Standby Function (External)
NET-46-16-04	Universal LED NCF / Batten Suspension Kit
NET-51-11-01	PIR Sensor (External) for Battens and NCFs

NET LED Lighting


 Buckingham Business Park, 300 Anderson Road,
 Swavesey, Cambridge, CB24 4UQ

 T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

ORDER BY 6PM
 FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	132lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	216
Driver Manufacturer	BOKE
Driver Output Voltage (DC)	30-42V
Total Circuit Power (W)	32W/40W +/- 5W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	1-10V Dimming
Flicker-Free	Yes
Operating Temp.	-15°C to +45°C
Lifespan LM80	43,000 Hours
UGR Rating	More than 19
Weight	2.15Kg
Manufacturer	Sochii Lighting
Fire Rating	V2
Housing Colour	Grey
Housing Material	Polycarbonate
Diffuser Material	Polycarbonate



Other Options

Description	
NET-43-11-03	Hilton NCF 5500K 1200mm (4ft) 32W/40W Standard

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk