

CAXTON DOWNLIGHT TRI-COLOUR 8" 20W TP(A) DIMMABLE SELF TEST

NET-49-05-29




Tridonic Excite Dimmable driver

Allows for one4all Dimming - DALI 1 & 2 and switchDIM options



Self Test Emergency operation

Save time and money with a fitting that carries out its own testing in line with relevant standards



Features & Benefits

- Self Test Emergency function
- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Ø200-210mm cut out size
- TP(a) flammability-rated diffuser
- Selectable 3000K, 4000K or 5500K colour temperature
- Shatterproof polycarbonate diffuser

Key Data

Power	20W
Luminous Flux	2100lm/2200lm/2100lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP65 Front/IP20 Rear
Dimensions	Ø228 x 45mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-42-43-24	DALI Dimmer Switch
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	105lm/W
LED Manufacturer	Honglitrronic
LED Type	SMD 2835
No. of LEDs	120
Driver Manufacturer	Tridonic Premium Series
Driver Output Voltage (DC)	30-44V
Total Circuit Power (W)	20W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	110°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	More than 19
Weight	0.87Kg
Manufacturer	CREP Optoelectronics
Hours Maintained	3H
Luminous Flux Factor	15%
Self Test	Yes
Cut-Out Size	ø200-210mm
Housing Colour	White
Housing Material	Aluminium
Battery Pack	LiFePO4 3.2V 4.5Ah
Dimming Input Type	Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)

Other Options

Description		
NET-49-05-76 Emergency Operation	>3H	Caxton Downlight Tri-Colour 8" 20W TP(a) Standard
NET-49-05-87 Emergency Self Test	Foxlux	Caxton Downlight Tri-Colour 8" 20W TP(a) Emergency
NET-49-05-88		Caxton Downlight Tri-Colour 8" 20W TP(a) Dimmable one4all
NET-49-05-89		Caxton Downlight Tri-Colour 8" 20W TP(a) Dimmable Emergency
NET-49-05-28		Caxton Downlight Tri-Colour 8" 20W TP(a) Self Test Emergency
NET-49-05-29		Caxton Downlight Tri-Colour 8" 20W TP(a) Dimmable Self Test Emergency
NET-49-05-30		Caxton Downlight Tri-Colour 8" 20W TP(a) Dimmable DALI Emergency



NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

 **ORDER BY 6PM**
FOR NEXT DAY DELIVERY

Ø90-210MM CUT-OUT SIZES

Available in 3", 4", 6" and 8",
these downlights are designed
to fit most existing holes

STAINLESS STEEL RETAINING CLIPS

Quick and simple installation
with no need for additional
tools



TRIDONIC DIMMABLE DRIVER


Customise lighting levels and
reduce electricity consumption

Dimmable options only



TP(A) FLAMMABILITY RATED DIFFUSER

Comply with Building Regulations
and prevent flaming particles



IP65 RATED FASCIA

Protect the downlight
from water and dust

SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent
the diffuser shattering into
small, indistinct pieces

SELECTABLE COLOUR TEMPERATURE

Choose your colour
temperature
3000K, 4000K or 5500K

3K

4K

5.5K

3H EMERGENCY OPERATION

Ensures the fitting comes
on in the event of a
power failure

Emergency options only

