

**CAXTON DOWNLIGHT TRI-COLOUR 3" 5W TP(A) EMERGENCY/SELF TEST**


NET-49-05-71


**3 Hour  
Emergency  
operation**

The integral Emergency Battery ensures the fitting stays on in the event of an emergency or power failure - can be Self Test Emergency or standard 3H Emergency


**Tri-Colour**

Choose your colour temperature (3000K, 4000K or 5500K) at the time of installation


**Features & Benefits**

- 3H Emergency function
- Ø90-100mm cut out size
- TP(a) flammability-rated diffuser
- Selectable 3000K, 4000K or 5500K colour temperature
- Shatterproof polycarbonate diffuser
- Stainless steel retaining clips

**Key Data**

<b>Power</b>	5W
<b>Luminous Flux</b>	475lm/500lm/470lm
<b>Colour Temperature</b>	3000K/4000K/5500K
<b>IP Rating</b>	IP65 Front/IP20 Rear
<b>Dimensions</b>	Ø110 x 45mm
<b>Warranty</b>	5 Years (Registration Required)

**Compatible Accessories**

NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

**NET LED Lighting**

 Buckingham Business Park, 300 Anderson Road,  
 Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk


**ORDER BY 6PM**  
 FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.5
Luminaire Efficacy	95lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	48
Driver Manufacturer	Tridonic Essence Series
Driver Output Voltage (DC)	29-42V
Total Circuit Power (W)	5W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	100°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	More than 19
Weight	0.29Kg
Manufacturer	CREP Optoelectronics
Hours Maintained	3H
Luminous Flux Factor	60%
Self Test	No
Cut-Out Size	ø90-100mm
Housing Colour	White
Housing Material	Aluminium
Battery Pack	LiFePO4 3.2V 4.5Ah
Emergency Kit	3 Year Warranty
Emergency Operation	>3H

Other Options



### Description

NET-49-05-70	Caxton Downlight Tri-Colour 3" 5W TP(a) Standard
NET-49-05-71	Caxton Downlight Tri-Colour 3" 5W TP(a) Emergency/Self Test

## NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Ø90-210MM CUT-OUT SIZES

Available in 3", 4", 6" and 8",  
these downlights are designed  
to fit most existing holes

### STAINLESS STEEL RETAINING CLIPS


Quick and simple installation  
with no need for additional  
tools



### TRIDONIC DIMMABLE DRIVER


Customise lighting levels and  
reduce electricity consumption

*Dimmable options only*



### TP(A) FLAMMABILITY RATED DIFFUSER

Comply with Building Regulations  
and prevent flaming particles



### IP65 RATED FASCIA

Protect the downlight  
from water and dust

### SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent  
the diffuser shattering into  
small, indistinct pieces



### SELECTABLE COLOUR TEMPERATURE

Choose your colour  
temperature 3000K,  
4000K or 5500K

3K

4K

5.5K

**NEW**

### MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual  
emergency or self test  
emergency at the time  
of installation

*Emergency options only*

