

CAMBRIDGE SURFACE LINEAR 30W/50W TRI COLOUR MICROWAVE SENSOR

NET-51-11-76



Integral Microwave Sensor

Save money and energy by ensuring the fitting only comes on when movement is detected



3 Hour Emergency operation

The integral Emergency Battery ensures the fitting stays on in the event of an emergency or power failure



Features & Benefits

- 3H Emergency function
- Integral On/Off Microwave Sensor ensures the fitting only comes on when movement is detected
- Selectable 3000K, 4000K or 5500K colour temperature
- Dual Wattage driver allows a choice between 30W or 50W
- Rear or end cable entry
- Self Test Emergency option available

Key Data

Power	30W/50W
Luminous Flux	5024lm/5000lm/6490lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP20
Dimensions	1500 x 215 x 77mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-42-43-10	Merrytek Daylight Switch (Internal)
NET-42-43-24	DALI Dimmer Switch
NET-51-11-02	Cambridge/Trinity Suspension Kit

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	130lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	720
Driver Manufacturer	Tridonic Advanced Series
Driver Output Voltage (DC)	60V
Total Circuit Power (W)	30W/50W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	3.2Kg
Manufacturer	Sealite Co. Ltd.
Fire Rating	V2
Hours Maintained	3H
Luminous Flux Factor	6%
Lux Levels	2lux - 50lux or Disabled
Max. Detection Distance	6m
Self Test	No
Housing Colour	White
Housing Material	Steel
Battery Pack	LiFePO4
Detection Angle	150°(wall mt) / 360°(ceiling mt)

PRODUCT DIMENSIONS



Other Options

		Description
Duration	NET-51-11-65	5s - 30min Cambridge Surface Linear 30W/50W Tri Colour Standard
Emergency	NET-51-11-67	3 Year Warranty Cambridge Surface Linear 30W/50W Tri Colour Emergency
Emergency Operation	NET-51-11-68	>3H Cambridge Surface Linear 30W/50W Tri Colour Self Test Emergency
Emergency Pack	NET-51-11-69	Streamer Cambridge Surface Linear 50W Tri Colour Dimmable one4all
Max. Detection Area	NET-51-11-70	6m Cambridge Surface Linear 50W Tri Colour Dimmable Emergency
Sensor Manufacturer	NET-51-11-71	Merrytek Cambridge Surface Linear 50W Tri Colour Dimmable Self Test Emergency
Sensor IP Rating	NET-51-11-72	IP20 Cambridge Surface Linear 50W Tri Colour Dimmable DALI Emergency
	NET-51-11-75	Cambridge Surface Linear 30W/50W Tri Colour Microwave Sensor
	NET-51-11-76	Cambridge Surface Linear 30W/50W Tri Colour Microwave Sensor Emergency
	NET-51-11-77	Cambridge Surface Linear 30W/50W Tri Colour Microwave Sensor Self Test Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

130
lm/W

3H EMERGENCY OPERATION

Ensures the fitting comes on in the event of a power failure

Emergency options only

HINGED DIFFUSER

Get quick and easy access to wiring

REAR OR END CABLE ENTRY

Create seamless end-to-end lighting designs

TRIDONIC PREMIUM DIMMABLE DRIVER

Customise lighting levels and reduce electricity consumption

Dimmable options only

INTEGRAL MICROWAVE SENSOR WITH 6M DETECTION DISTANCE AND 5S-30MIN HOLD TIME

Save energy costs with a fitting that only lights the room when movement is detected

Microwave Sensor options only

DUAL WATTAGE TRIDONIC DRIVER

Choose between 38W or 50W at the time of installation

Standard, Emergency and Microwave Sensor options only

3K

4K

5.5K

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K