

Insert, red, blank RMQ16

Cat Number: 04TQ25



Eaton Moeller® series RMQ16 Button plate, 25 x 25 mm, red

Technical Specifications:

Product Length/Depth | 3 mm

Product Height | 19 mm

Product Width | 19 mm

Product Weight | 0.002 kg

Certifications | UL/CSA certification not required

Color | Red

Inscription | None

Shape | Square

Product Category | Accessories

Size | 25 × 25 mm

Suitable for | Push button

Ambient operating temperature - min | -25 °C

Ambient operating temperature - max | 60 °C

Connection to SmartWire-DT | No

Equipment heat dissipation, current-dependent P<sub>vid</sub> | 0 W

Heat dissipation capacity  $P_{diss}$  | 0 W

Heat dissipation per pole, current-dependent  $P_{vid}$  | 0 W

Rated operational current for specified heat dissipation ( $I_n$ ) | 0 A

Static heat dissipation, non-current-dependent  $P_{vs}$  | 0 W

10.2.2 Corrosion resistance | Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation | Please enquire

10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions | Meets the product standard's requirements.

10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances | Meets the product standard's requirements.

10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections | Is the panel builder's responsibility.

10.8 Connections for external conductors | Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength | Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage | Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility.

10.10 Temperature rise | Not applicable.

10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.