

MCCB NZM2 3pole 160A 36kA therm/mag

Cat Number: NZMC2-A160



Eaton Moeller series NZM - Molded Case Circuit Breaker. NZM2, 3 pole, Icu 400/415 V 50 Hz (Icu): 36 kA, 160 A, thermo magnetic, Fixed, Screw connection, IEC

Technical Specifications:

Product Length/Depth | 149 mm

Product Height | 184 mm

Product Width | 105 mm

Product Weight | 2.348 kg

Compliances | RoHS conform

Certifications | IEC/EN 60947

IEC

Rated operational current for specified heat dissipation (In) | 160 A

10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz | 4 kA

10.4 Clearances and creepage distances | Meets the product standard's requirements.

10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting Method | DIN rail (top hat rail) mounting optional

Fixed

Built-in device fixed built-in technique

Amperage Rating | 160 A

10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (copper strip) | Max. 8 segments of 24 mm x 1 mm (2x) at box terminal

Max. 10 segments of 16 mm x 0.8 mm at box terminal

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Max. 10 segments of 24 mm x 0.8 mm at rear-side connection (punched)

Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched)

Handle type | Rocker lever

10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements.

Ambient storage temperature - min | 40 °C

Protection against direct contact | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110

Terminal capacity (copper busbar) | Min. 16 mm x 5 mm direct at switch rear-side connection

M8 at rear-side screw connection

Max. 24 mm x 8 mm direct at switch rear-side connection

10.8 Connections for external conductors | Is the panel builder's responsibility.

Special features | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})

Rated current = rated uninterrupted current: 160 A

Ambient operating temperature - max | 70 °C

Position of connection for main current circuit | Front side

Rated insulation voltage (U_i) | 690 V AC

Climatic proofing | Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Terminal capacity (copper stranded conductor/cable) | 25 mm² - 70 mm² (2x) direct at switch rear-side connection

25 mm² - 185 mm² (1x) direct at switch rear-side connection

25 mm² - 70 mm² (2x) at box terminal

25 mm² - 185 mm² (1x) at 1-hole tunnel terminal

25 mm² - 185 mm² (1x) at box terminal

Features | Protection unit

Motor drive optional

Lifespan, electrical | 7500 operations at 415 V AC-1

5000 operations at 690 V AC-1

10000 operations at 400 V AC-1

Electrical connection type of main circuit | Screw connection

Short-circuit total breaktime | < 10 ms

Rated impulse withstand voltage (U_{imp}) at main contacts | 8000 V

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz | 36 kA

10.9.3 Impulse withstand voltage | Is the panel builder's responsibility.

Utilization category | A (IEC/EN 60947-2)

Number of poles | Three-pole

Ambient operating temperature - min | -25 °C

10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (control cable) | 0.75 mm² - 2.5 mm² (1x)

0.75 mm² - 1.5 mm² (2x)

Equipment heat dissipation, current-dependent | 38.4 W

Instantaneous current setting (I_i) - min | 960 A

10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility.

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 230 V, 50/60 Hz | 55 kA

Application | Use in unearthed supply systems at 690 V

10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated.

Rated short-circuit making capacity I_{cm} at 240 V, 50/60 Hz | 121 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 440 V, 50/60 Hz | 22.5 kA

Degree of protection (IP), front side | IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

Rated short-circuit making capacity I_{cm} at 525 V, 50/60 Hz | 24 kA

Rated short-circuit making capacity I_{cm} at 690 V, 50/60 Hz | 14 kA

Instantaneous current setting (Ii) - max | 1600 A

Overload current setting (Ir) - min | 125 A

Short delay current setting (I_{sd}) - min | 0 A

Number of auxiliary contacts (normally closed contacts) | 0

10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.

Lifespan, mechanical | 20000 operations

Overload current setting (Ir) - max | 160 A

Voltage rating | 690 V - 690 V

Terminal capacity (copper solid conductor/cable) | 6 mm² - 16 mm² (2x) at box terminal

10 mm² - 16 mm² (1x) at box terminal

10 mm² - 16 mm² (1x) direct at switch rear-side connection

6 mm² - 16 mm² (2x) direct at switch rear-side connection

16 mm² (1x) at tunnel terminal

Degree of protection (terminations) | IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Terminal capacity (aluminum stranded conductor/cable) | 25 mm² - 185 mm² (1x) at tunnel terminal

10.9.2 Power-frequency electric strength | Is the panel builder's responsibility.

Short-circuit release non-delayed setting - min | 960 A

Degree of protection | IP20 (basic degree of protection, in the operating controls area)
IP20

Overvoltage category | III

Rated short-time withstand current (t = 1 s) | 85 kA

Short delay current setting (I_{sd}) - max | 0 A

Rated impulse withstand voltage (U_{imp}) at auxiliary contacts | 6000 V

Number of auxiliary contacts (change-over contacts) | 0

Ambient storage temperature - max | 70 °C

Release system | Thermomagnetic release

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 525 V, 50/60 Hz | 6 kA

Optional terminals | Box terminal. Connection on rear. Tunnel terminal

Pollution degree | 3

10.7 Internal electrical circuits and connections | Is the panel builder's responsibility.

10.10 Temperature rise | The panel builder is responsible for the temperature rise calculation.

Eaton will provide heat dissipation data for the devices.

Functions | System and cable protection

Short-circuit release non-delayed setting - max | 1600 A

Rated short-circuit making capacity I_{cm} at 400/415 V, 50/60 Hz | 76 kA

Standard terminals | Screw terminal

Type | Circuit breaker

10.2.2 Corrosion resistance | Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements.

10.2.7 Inscriptions | Meets the product standard's requirements.

Rated short-circuit making capacity I_{cm} at 440 V, 50/60 Hz | 63 kA

Number of auxiliary contacts (normally open contacts) | 0

Isolation | 300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

Number of operations per hour - max | 120

Circuit breaker frame type | NZM2

Direction of incoming supply | As required

Shock resistance | 20 g (half-sinusoidal shock 20 ms)

Terminal capacity (aluminum solid conductor/cable) | 16 mm² (1x) at tunnel terminal