

RTECH MR SEO ATF 200 MNM 3H IP65

Cat Number: RT2RSEO200ATF3HIP



EATON'S ROUNDTech MEDIUM RECES. SAFETY EFOCUS ATF 200 MNM 3H IP65

Technical Specifications:

Product Length/Depth | 44 mm

Product Height | 110 mm

Product Width | 110 mm

Product Weight | 0.325 kg

Certifications | CE marking

CE

Conductor cross section | 2.5

Lamp holder | None

Permissible ambient temperature - max | 45 °C

Rated Luminous Flux Acc. IEC 62722-2-1 | 200 lm

Testing system | Auto-Test

Mounting Method | Surface mounting/recessed mounting

Outer diameter | 110 mm

Monitoring equipment | Automatic self test

Battery number of cells | 2

Luminous flux in standby mode | 60 lm
Nominal voltage AC - min | 230 V
Light distributor | Focal lens
Suitable for number of lamps | 2
Color rendering index (CRI) | 70
Explosion protected | False
Nominal voltage AC - max | 230 V
Built-in Width | 110 mm
Built-in height/depth | 200 mm
Built-in Length | 200 mm
Kind of luminaire | Safety luminaire for escape route and open area lighting
Power supply system | Peripheral (individual battery)
Rated life time L70/B10 at 25 °C | 60600 hour
Data connection terminal | 0,5-2,5 mm²
Application | Other
Voltage type | AC
Color housing | White
Wiring system | Continuous circuit/emergency circuit
Shape | Round
Glow wire test | 850 °C
Impact strength | IK05
Rated life time L90/B10 at 25 °C | 60600 hour
Color temperature - min | 5700 K
Mode | Maintained / Non-Maintained (M / NM)
Protection class | II
Material cover | Plastic, transparent
Function | Escape route lighting
Battery quality | Lithium-ions
Battery voltage | 3.2 V
With light source | True
Connection type | Plug-in connection
Outdoor use compliance | False
Pictogram included | False
Color temperature - max | 5700 K
Diameter | 110 mm

Degree of protection | IP65
Main connection terminal | 0,5-2,5 mm²
Reserve-polarity protected | False
Rated life time L80/B10 at 25 °C | 60600 hour
Limited surface temperature | False
Nominal operation time - max | 3 hour
Built-in Diameter | 64 mm
Lamp type | LED not exchangeable
With remote switch connection | True
Number Of Poles (Numeric) | 3
Type of indicator | Not applicable
Color of light | White
Max. system power | 1.1 W
Nominal operation time - min | 3 hour
Material housing | Plastic
Power factor | .6
Number of lighting heads | 1
Frequency | 50/60 Hz
Number of LEDs | 8
Permissible ambient temperature - min | 5 °C
Apparent Power At Mains Operation | 1.83 VA
Energy efficiency class of the built-in lamp | A++, A+, A (LED)