



Remote server management that enables secure remote computer access using your standard IP network

The ADDERLink® ipeps enables you to remotely access and control your critical computing hardware using your standard IP network. KVM connections are VGA and PS/2. Using RealVNC® client software, computers outside the network can be remotely and securely accessed.

ADDERLink® ipeps

RealVNC Server with RFB 3.3 Support

Up to four users can remotely and securely access computers outside your network, with the possibility of creating 16 user profiles with defined access rights.

USB and Virtual Media Support

Engineered to act as a conduit through which data can be passed so that files can be transferred via IP onto the ipeps and onto the target computer by means of a USB virtual media port.

Enterprise Management Software

ADDER.NET provides a centralized, secure and intuitive user access management interface, where up to 16 user profiles with defined access rights can be created.

High Performance Video over VNC

RealVNC enables video resolutions of up to 1600x1200, as it is free of the limitations of HTTPS.

Independent Operation

Maintain full control even during boot up, BIOS level or computer crash states, it will work even if the controlled devices are not operational.



ADDER® ADDERLink® ipeps



Video Information (1 Screen)

Maximum Resolution (1 Screen)	1600 x 1200
--------------------------------------	-------------

Video Additional Information

Video Additional Information	Supports standard PC, Sun and Mac video modes up to resolutions of 1600 x 1200 with scalable viewer.
-------------------------------------	--

Computer Connections

VGA	1x
------------	----

PS/2	2x
-------------	----

	2x
--	----

Link Ports

8p8c (RJ45)	1x
--------------------	----

Network Support

10/100 Support	Yes
-----------------------	-----

Environmental

Operating Temperature Range °C / °F	0 to 40 °C / 32 to 104 °F
--	---------------------------

Power Source

5V	1x
-----------	----

Physical Design

Construction Material	Robust metal construction
------------------------------	---------------------------

Width (mm) / (in.)	120 / 4.7
---------------------------	-----------

Height (mm) / (in.)	27 / 1.1
----------------------------	----------

Depth (mm) / (in.)	75 / 3
---------------------------	--------

Weight (kg) / (lb)	0.34 / 0.7
---------------------------	------------

Front Panel Features

Single color status LEDs	6x
--------------------------	----

Compatibility

OS Compatibility	Windows, DOS, Linux, Unix, BSD, Sun OS, macOS, NetWare, All known operating systems
-------------------------	---

Approvals and Standards

Approvals	CE, FCC, KC
------------------	-------------



ADDER[®] ADDERLink[®] ipeps

What's in the Box?

1x VKVM-1M KVM cable set

1x USB convertor plugs

Ordering Information

AL-IPEPS-XX

IPEPS SINGLE

Related Accessories (Sold Separately)

ADDER[®] CCSUN

ADDER[®] Rackmount Chassis ALAV-RMK-CHASSIS

ADDER[®] Power Supply Unit 5volt DC 2.5A

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.