



A single-link, single-head digital video and USB2.0 fanless KVM extender that runs over a single cable using your standard IP network.

ADDERLink® INFINITY 1002 is a high performance KVM extender that forms part of the ADDERLink INFINITY matrix solution. This enables you to locate your critical computing hardware in a secure and temperature controlled environment away from the user work station, while maintaining a pixel-perfect desktop experience.

## ADDERLink® INFINITY 1002T

Matrix

### Features



#### Perfect Digital Video, Real-Time Control

Using a spatially-lossless encoding system, with 1:1 pixel mapping, ADDERLink INFINITY provides pixel-perfect and color accurate video with no artefacts. The digital video you receive is the same as the digital video leaving the remote computer.



#### Standard IP Technology

Using standard IP technology allows a choice of CATx or fiber connections. Resilience is offered by the optional 2nd network port which provides teaming facility for load balanced and critical systems.



#### Unlimited Extension Distances

Extension distance is not limited to a single 100 meter cable length. If you need to extend further, simply add a 1GbE network device to achieve an additional 100 meters, which can be repeated many times. Also fitted with SFP cages to accept fiber optic transceivers for much greater distances.



#### USB 2.0 with Class Control

Supports USB devices including graphics tablets, jog shuttles, joysticks and 3D explorers, alongside mass storage devices. For secure applications, the system can disable the use of non-HID devices, meaning there is no need to physically block USB ports to prevent the use of mass storage devices.



#### Support for Dithered Video

Allows analog or noisy video to pass through the system along with computers that dither the video to enhance the perceptive image quality. Some Mac computers use this technique.



#### ADDERLink INFINITY Matrix

With the addition of the ADDERLink INFINITY Management (AIM) system, you can turn multiple point-to-point extenders into a scalable digital KVM matrix system that allows any workstation to link with any computer connected to the network.



### **EDID Management**

Intelligent EDID management allows the true characteristics of the monitor to be passed back to the computer. This ensures perfect video display without additional configuration.



### **Plug and Play**

ADDERLink INFINITY devices are delivered in a zero config state so you can plug them in and start working on them straight away. There is no need for drivers or software to be installed.



### **Redundant Network Operation**

The units support network teaming allowing for full network redundancy and increased resilience for mission-critical applications.

### **Analog Audio**

The ALIF1002 supports bi-directional stereo audio input via 3.5mm jack connectors.

<b>Video Information (1 Screen)</b>	
Maximum Resolution (1 Screen)	1920 x1200
Frame Rate (1 Screen)	60
Color Depth (1 Screen)	8 bpc
<b>Computer Connections</b>	
USB B	1x 2.0, True Emulation,High Speed
DVI-D	1x
<b>Link Ports</b>	
8p8c (RJ45)	1x
SFP	1x
<b>Serial Ports</b>	
Serial Connection	1x RS232
Maximum Baud Rate	115,200
Serial Additional Information	RS232 9-pin D-type
<b>Audio Connections</b>	
Audio Type	Analog
Channels	2x
Audio Direction	Bi-directional
Size (bit)	16
Speed (kHz)	48
Audio In Port	1x 3.5mm jack
Audio Out Port	1x 3.5mm jack
<b>Network Support</b>	
Bandwidth	1GbE
10/100 Support	No
<b>Environmental</b>	
Operating Temperature Range °C / °F	0 to 40 °C / 32 to 104 °F
Storage Temperature °C / °F Range	0 to 40 °C / 32 to 104 °F
Operating Humidity (%)	5% - 90% (non-condensing)
Storage Humidity (%)	-10% - 90% (non-condensing)
Altitude m/ft	2,000 / 6562
Mean Time Between Failure (MTBF)	700,000 h
MTBF Standard	Telcordia SR332 Issue 4 March 2016 Calculated @ 55C

<b>Temperature Regulation</b>	Fanless
<b>Power Source</b>	
<b>5V</b>	1x
<b>Input Power Supply</b>	External Power Supply Unit (see manual)
<b>Power Consumption</b>	
<b>Maximum Power (Watts)</b>	20
<b>Typical Power (Watts)</b>	10
<b>Physical Design</b>	
<b>Construction Material</b>	Robust metal construction
<b>U size</b>	1
<b>Width (mm) / (in.)</b>	198 / 7.8
<b>Height (mm) / (in.)</b>	44 / 1.7
<b>Depth (mm) / (in.)</b>	150 / 5.9
<b>Weight (kg) / (lb)</b>	1.1 / 2.4
<b>Compatibility</b>	
<b>OS Compatibility</b>	All known operating systems
<b>Approvals and Standards</b>	
<b>Approvals</b>	CE, cULus - E476334, FCC, ICES, RCM, UKCA
<b>Standards</b>	ANSI 63.4, EN55032 /CISPR 32, EN55035/CISPR 35, EN63000, FCC pt15B, ICES003
<b>Other</b>	Cal Prop 65, China ROHS, EU REACH, UK REACH



### What's in the Box?

1x ALIF1002 Transmitter

1x PSU-IEC-5VDC-4A: Mains power supply

1x IEC PSU cable of country code

1x VSCD1: 2m/6.5ft Single link DVI cable

1x VSC24: 2m/6.5ft USB cable

2x VSC22: 2m/6.5ft Audio cable

### Ordering Information

ALIF1002T-XX                      ALIF1002 Transmitter

### Related Accessories (Sold Separately)

ADDER® Rack Mount Kit RMK4S

ADDER® DVI-D Single-Link Cable

ADDER® Rackmount Kit RMK4D-R2

ADDER® VSC24 USB Cable

ADDER® Rackmount Kit RMK4V

ADDER® SFP-SM-LC

ADDER® SFP-CATX-RJ45

ADDER® SFP-MM-LC

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.