





A dual-link, dual-head digital video and USB fanless KVM extender that runs over a single cable on your standard IP network. Available with fiber access modules.

ADDERLink INFINITY Dual is a high performance KVM extender that forms part of the ADDERLink INFINITY Range. This enables you to locate your critical computing hardware in a secure and temperature controlled environment away from the user work station, while maintaining a pixel-perfect desktop experience.

ADDERLink® INFINITY Dual 2002

Perfect Digital Video, Real-time control

Using a spatially-lossless encoding system, with 1:1 pixel mapping, ADDERLink INFINITY provides pixel-perfect and color accurate video with no artefacts. The digital video you receive is the same as the digital video leaving the remote computer.

Unlimited Extension Distances

Extension distance is not limited to a single 100 meter cable length. If you need to extend further, simply add a 1GbE network device to achieve an additional 100 meters, which can be repeated many times. Also fitted with SFP cages to accept fiber optic transceivers for much greater distances.

USB 2.0 with Class Control

Supports USB devices including graphics tablets, jog shuttles, joysticks and 3D explorers, alongside mass storage devices. For secure applications, the system can disable the use of non-HID devices, meaning there is no need to physically block USB ports to prevent the use of mass storage devices.

Single CATx Cable or Fiber with Immunity from Interference

Using standard IP technology allows a choice of single structured cable (CATx) or fiber connection achieving reliable links without interference.

Support for Mac Pro® (Dithered Video)

A "dithering" technique seen with graphics cards can give the appearance of a deeper color depth than is true, which can significantly increase the normal video data rates. ALIF2002T has a "Magic Eye" feature which supports dithering without allowing it to degrade overall link performance.

ADDERLink INFINITY Matrix

With the addition of the ADDERLink INFINITY management system (AIM), you can turn multiple point-to-point extenders into a scalable digital KVM matrix system that allows any workstation to link with any computer connected to the network. See the AIM datasheet for details.





EDID Management

Intelligent EDID management allows the true characteristics of the monitor to be passed back to the computer. This ensures perfect video display without the additional configuration.

Redundant Network Operation

The units support network teaming allowing for full network redundancy and increased resilience for mission-critical applications.

Plug and Play

ADDERLink INFINITY devices are delivered in a zero config state so you can plug them in and start working on them straight away. There is no need for drivers or software to be installed.

Analog Audio

The ALIF2002 supports bi-directional stereo audio input via 3.5mm jack connectors.

Video Information (1 Screen)	
Maximum Resolution (1 Screen)	2560 x1600
Frame Rate (1 Screen)	60 Hz
Color Depth (1 Screen)	8 bpc

Video Information (2 Screen)	
Maximum Resolution (2 Screens)	1920 x 1200
Frame Rate (2 Screens)	60 Hz
Color Depth (2 Screen)	8 bpc

Video Additional Information	
Video Additional Information	The system supports either two Single Link DVI-D resolutions to a maximum of 1920 x1200 @ 60Hz or one Dual Link to a maximum of 2560 x1600 @ 60Hz

Computer Connections	
USB B	1x ,
DVI-D	2x

Link Ports	
8p8c (RJ45)	1x
SFP	1x

Serial Ports	
Serial Connection	1x RS232
Maximum Baud Rate	115,200
Serial Additional Information	RS232 can be passed between the units to a maximum baud rate 115K2.

Audio Connections	
Audio Type	Analog
Channels	2x
Audio Direction	Bi-directional
Size (bit)	16
Speed (kHz)	48
Audio In Port	1x 3.5mm jack
Audio Out Port	1x 3.5mm jack

Network Support

Bandwidth	1GbE
10/100 Support	No

Environmental	
Operating Temperature Range °C / °F	0 to 40 °C / 32 to 104 °F
Storage Temperature °C / °F Range	0 to 40 °C / 32 to 104 °F
Operating Humidity (%)	10% - 90% (non-condensing)
Altitude m/ft	2,000 / 6562
Mean Time Between Failure (MTBF)	500,000 h
MTBF Standard	Telcordia SR332 Issue 4 March 2016 Calculated @ 55C
Temperature Regulation	Fanless

Power Source	
5V	1x

Power Consumption	
Maximum Power (Watts)	20
Typical Power (Watts)	12

Physical Design	
Construction Material	Robust metal construction
U size	1
Width (mm) / (in.)	198 / 7.8
Height (mm) / (in.)	44 / 1.7
Depth (mm) / (in.)	150 / 5.9
Weight (kg) / (lb)	1.1 / 2.4

Compatibility	
OS Compatibility	All known operating systems
System Requirements	Isochronous devices are not supported (e.g. USB audio or video devices).

Approvals and Standards	
Approvals	CE, cULus - E476334, FCC, ICES, RCM, UKCA
Standards	ANSI 63.4, BSEN60950, EN55032 /CISPR 32, EN55035/CISPR 35, EN61000-3-2, EN61000-3-3, EN63000, FCC pt15B, ICES003
Other	Cal Prop 65, China ROHS, EU REACH, UK REACH

What's in the Box?
1x ALIF Dual 2002T
1x PSU-IEC-5VDC-4A: Mains power supply
1x IEC PSU cable of country code
1x VSCD3: 2m/6.5ft Dual link DVI cable
1x VSCD1: 2m/6.5ft Single link DVI cable
1x VSC24: 2m/6.5ft USB cable
2x VSC22: 2m/6.5ft Audio cable

Ordering Information	
ALIF2002T-XX	ALIF2002 Transmitter

Related Accessories (Sold Separately)
ADDER® Rack Mount Kit RMK4S
ADDER® Rackmount Kit RMK4D-R2
ADDER® Rackmount Kit RMK4V
ADDER® SFP-SM-LC
ADDER® SFP-CATX-RJ45
ADDER® SFP-MM-LC

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.

Copyright 2026 | Adder Technology Ltd.