



Dual-head digital video, audio, and USB2.0 over 1GbE IP network.

A high performance KVM extender that allows critical computing hardware to be stored in a secure and temperature-controlled environment, while providing an 'at-the-PC' experience across distances up to 20km. The solution can be used as a point-to-point extender or integrated into a matrix system with the ADDERLink® INFINITY Manager (AIM).

## ADDERLink® INFINITY Dual 2020T

Matrix

### Features



#### Perfect Digital Video, Real-Time Control

Using a spatially-lossless encoding system, with 1:1 pixel mapping, ADDERLink INFINITY provides pixel-perfect and color accurate video with no artefacts. The digital video received is the same as the digital video leaving the remote computer.



#### Standard IP Technology

Using standard IP technology allows a choice of single structured cable (CATx) or fiber connection achieving reliable links without interference. The ADDERLink INFINITY Dual 2020 also offers the option of up to 20km distances with fiber.



#### Unlimited Extension Distances

Extension distance is not limited to a single 100 meter cable length. If you need to extend further, simply add a 1GbE network device to achieve an additional 100 meters, which can be repeated many times. Also fitted with SFP cages to accept fiber optic transceivers for much greater distances.



#### MacPro

#### Support for Mac Pro® (Dithered Video)

A "dithering" technique seen with graphics cards can give the appearance of a deeper color depth than is true, which can significantly increase the normal video data rates. ALIF2020 has a "Magic Eye" feature which supports dithering without allowing it to degrade overall link performance.



#### USB 2.0 with Class Control

Supports USB devices including graphics tablets, jog shuttles, joysticks and 3D explorers, alongside mass storage devices. For secure applications, the system can disable the use of non-HID devices, meaning there is no need to physically block USB ports to prevent the use of mass storage devices.



#### ADDERLink INFINITY Matrix

With the addition of the ADDERLink INFINITY management system (AIM) you can turn multiple point-to-point extenders into a scalable digital KVM matrix system that allows any workstation to link with any computer connected to the network. See the AIM datasheet for details.



### **EDID Management**

Intelligent EDID management allows the true characteristics of the monitor to be passed back to the computer. This ensures perfect video display without additional configuration.



### **Plug and Play**

ADDERLink INFINITY devices are delivered in a zero config state so you can plug them in and start working on them straight away. There is no need for drivers or software to be installed.



### **Redundant Network Operation**

The units support network teaming allowing for full network redundancy and increased resilience for mission-critical applications.



### **Analog Audio**

The ALIF2020 supports bi-directional stereo audio input via 3.5mm jack connectors.

<b>Video Information (1 Screen)</b>		
Maximum Resolution (1 Screen)		1920 x 1200
Frame Rate (1 Screen)		60 Hz
Color Depth (1 Screen)		8 bpc
<b>Video Information (2 Screen)</b>		
Maximum Resolution (2 Screens)		1920 x 1200
Frame Rate (2 Screens)		60 Hz
Color Depth (2 Screen)		8 bpc
<b>Video Additional Information</b>		
Video Additional Information		The system supports two Single Link DVI-D resolutions to a maximum of 1920 x 1200 @ 60Hz.
<b>Computer Connections</b>		
USB B		1x , True Emulation,High Speed
DVI-D		2x
<b>Link Ports</b>		
8p8c (RJ45)		1x
SFP		1x
<b>Serial Ports</b>		
Serial Connection		1x RS232
Maximum Baud Rate		115,200
Serial Additional Information		RS232 can be passed between the units to a maximum baud rate 115K2.
<b>Audio Connections</b>		
Audio Type		Analog
Channels		2x
Audio Direction		Bi-directional
Size (bit)		16
Speed (kHz)		48
Audio In Port		1x 3.5mm jack
Audio Out Port		1x 3.5mm jack
<b>Network Support</b>		
Bandwidth		1GbE
10/100 Support		No
<b>Environmental</b>		

Operating Temperature Range °C / °F	0 to 40 °C / 32 to 104 °F
Storage Temperature °C / °F Range	0 to 40 °C / 32 to 104 °F
Operating Humidity (%)	10% - 90% (non-condensing)
Altitude m/ft	2,000 / 6562
Mean Time Between Failure (MTBF)	600,000 h
MTBF Standard	Telcordia SR332 Issue 4 March 2016 Calculated @ 55C
Temperature Regulation	Fanless
<b>Power Source</b>	
5V	1x
<b>Power Consumption</b>	
Maximum Power (Watts)	20
Typical Power (Watts)	12
<b>Physical Design</b>	
Construction Material	Robust metal construction
U size	1
Width (mm) / (in.)	198 / 7.8
Height (mm) / (in.)	44 / 1.7
Depth (mm) / (in.)	150 / 5.9
Weight (kg) / (lb)	1.1 / 2.4
<b>Compatibility</b>	
OS Compatibility	All known operating systems
System Requirements	Isochronous USB devices are not supported (e.g. USB audio or video devices).
<b>Approvals and Standards</b>	
Approvals	CE, cULus - E476334, FCC, ICES, RCM, UKCA
Standards	ANSI 63.4, EN/IEC 62368-1, EN55032 /CISPR 32, EN55035/CISPR 35, EN61000-3-2, EN61000-3-3, EN63000, FCC pt15B, ICES003
Other	Cal Prop 65, China ROHS, EU REACH, UK REACH



### What's in the Box?

1x ALIF2020 Transmitter

1x PSU-IEC-5VDC-4A: Mains power supply

1x IEC PSU cable of country code

2x VSCD1: 2m/6.5ft Single link DVI cable

1x VSC24: 2m/6.5ft USB cable

2x VSC22: 2m/6.5ft Audio cable

### Ordering Information

ALIF2020T-XX                      ALIF2020 Transmitter

### Related Accessories (Sold Separately)

ADDER® Rack Mount Kit RMK4S

ADDER® Rackmount Kit RMK4D-R2

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.