



Flexible KVMA switch for sharing high resolution triple-head VGA video, audio and USB between multiple sources.

Enables four computers to be controlled from a single high resolution console using VGA connections. USB True Emulation technology enables USB HID devices to be continuously emulated to each computer for instantaneous and reliable hotkey switching. Option to attach selected peripherals to different computers.

ADDERView® 4 PRO VGA TRIPLE

High resolution video

VGA capabilities enable users to work at high resolutions including WUXGA (1920x1200) or 1920x1440.

Hi-speed USB2.0 device support

A wide range of USB devices can be connected, including printers, scanners and non-standard human interface devices.

Channel selection options

Switch using keyboard hotkeys, three button mouse, front panel controls or add an RC4 remote.

Extended DDC EDID profile

Ensures that the graphics card is always optimized to work with your screen.

USB HID True Emulation

Enables full support for hotkey and mouse switching and use of any USB human interface device from mice and keyboards through to graphics tablets, jog shuttles and joysticks.

Independent peripheral selection

Switching options enable the operator to use the keyboard and mouse on one computer while the USB peripherals are connected to other ones.



ADDER® ADDERView® 4 PRO VGA TRIPLE



Options port

Allows remote switching and firmware upgrades, all through the same port. Switching can be achieved using ADDER® RC4 remote or simple ASCII codes and units can also be linked to create a multi video head switching system.

Video Information (1 Screen)

Maximum Resolution (1 Screen) 1920 x 1440

Frame Rate (1 Screen) 60

Computer Connections

USB B 4x 2.0, Transparent,High Speed

VGA 12x

Console Connections

USB A 2x 2.0, True Emulation (HID Only),High Speed

USB A 2x 2.0, Transparent,High Speed

VGA 3x

Serial Ports

Serial Connection 1x RS232

Serial Additional Information Options port for switching, linking or upgrading

Serial Connection Type (console) RJ48 (10p10c)

Audio Connections

Audio Type Analog

Channels 2x

Audio Direction Output only

Size (bit) 0

Speed (kHz) 0

Audio In Port 4x 3.5mm jack

Audio Out Port 1x 3.5mm jack

Environmental

Operating Temperature Range °C / °F 0 to 40 °C / 32 to 104 °F

Storage Temperature °C / °F Range 0 to 40 °C / 32 to 104 °F

Operating Humidity (%) 10% - 90% (non-condensing)

Storage Humidity (%) 5% - 95% (non-condensing)

Altitude m/ft 2,000 / 6562

Mean Time Between Failure (MTBF) 900,000 h

MTBF Standard Telcordia SR332 Issue 4 March 2016 Calculated @ 55C

Power Source

5V 1x

Input Power Supply	2.5mm Socket
Power Additional Information	2.5mm jack 5VDC 2A
Physical Design	
Construction Material	Robust metal case
U size	2.5
Width (mm) / (in.)	260 / 10.2
Height (mm) / (in.)	100 / 3.9
Depth (mm) / (in.)	150 / 5.9
Front Panel Features	
Single color status LEDs	4x
Compatibility	
OS Compatibility	Windows, Linux, Sun OS, macOS, All known operating systems
Approvals and Standards	
Approvals	CE, FCC
Standards	ANSI 63.4, EN55032 /CISPR 32, EN55035/CISPR 35, EN63000, FCC - CFR47 pt15a
Other	Cal Prop 65, China ROHS, EU REACH, UK REACH, TSCA PFAS Section 8(a)7, TSCA PBT Section 6(h)



ADDERView® 4 PRO VGA TRIPLE

What's in the Box?

1x AV4PRO-DVI switch

1x Power supply unit

1x Country specific power cable

1x Quick start guide

Ordering Information

AV4PRO-VGA-TRIPLE-XX ADDERView® 4 PRO VGA 4 port triple-head switch

Related Accessories (Sold Separately)

ADDER® Rackmount Kit RMK3

ADDER® Remote Control RC4-8P8C

ADDER® VSC24 USB Cable

ADDER® Rackmount Kit RMK5PRO-MS

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.