



**High performance KVM over IP that delivers a complete, secure, non-blocking approach to remote server management.**

A powerful and flexible KVM over IP product contained within a compact unit, the ADDERLink® ipeps mini enables computer access from anywhere in the world, securely and remotely via the internet or a corporate network. The ipeps mini uses RealVNC® client software that is specifically designed for secure, high performance KVM over IP applications.

## ADDERLink® ipeps mini - DP

Remote

### Features



#### Independent Operation

Gives full control even during boot up, BIOS level or computer crash states. The ADDERLink ipeps mini will work even if the controlled device is not operational.



#### High Video Performance

The ipeps mini accepts a DP input up to 1920x1200 resolution. It incorporates VNC® Viewer from RealVNC, providing high streaming performance, subject to network bandwidth and content.




#### Highly Secure

Enterprise grade security (using AES 128 or 256-bit encryption and RSA 2048-bit public key authentication) is employed as standard. This is further enhanced by VNC, which allows the creation of ciphered user communications.




#### User Management

The ipeps mini can create up to 16 user profiles with defined access rights. Up to eight remote users may access the unit simultaneously.



### **EDID Management**

The ipeps mini has intelligent EDID management allowing the user to specify the video modes generated by the controlled device.



### **Remote Gateway**

The ipeps mini may be used as a remote gateway into the ADDERLink INFINITY, DDX and XDIP matrix systems, plus the ADDERView® 4 PRO Switch. This will allow remote users to access any computer connected to the switch.

Video Information (1 Screen)	
Maximum Resolution (1 Screen)	The system supports resolutions up to 1920x1200
Color Depth (1 Screen)	8 bpc
Computer Connections	
USB A	2x 2.0, True Emulation, Full Speed, Low Speed, High Speed
Full Size DisplayPort	1x 1.1 (dual mode)
Link Ports	
8p8c (RJ45)	1x
Network Support	
Bandwidth	1GbE
10/100 Support	No
Environmental	
Operating Temperature Range °C / °F	0 - 50 °C / 32 - 122 °F
Storage Temperature °C / °F Range	-10 - 60 °C / 14 - 140 °F
Operating Humidity (%)	10% - 90% (non-condensing)
Storage Humidity (%)	10% - 90% (non-condensing)
Altitude m/ft	2,000 / 6561.7
Mean Time Between Failure (MTBF)	2,000,000 h
Warranty	2 y
Power Source	
USB powered	2x
5V	1x
Power Additional Information	USB power: 2x USB2.0 (2x 500mA @5V) 5W• External power: 5VDC, 1A, (LPS)
Power Consumption	
Maximum Power (Watts)	5
Maximum Power (Current)	1
Typical Power (Watts)	3
BTU (BTU/hr)	10.2
Physical Design	
Construction Material	ABS and aluminium construction
U size	0
Width (mm) / (in.)	55 / 2.2

<b>Height (mm) / (in.)</b>	25 / 1
<b>Depth (mm) / (in.)</b>	110 / 4.3
<b>Flying Lead Length (mm)</b>	300
<b>Weight (kg) / (lb)</b>	0.2 / 0.4
<b>Compatibility</b>	
<b>OS Compatibility</b>	All known operating systems
<b>Approvals and Standards</b>	
<b>Approvals</b>	CE, cULus - E476334, FCC, ICES, KC, UKCA
<b>Standards</b>	ANSI 63.4, EN55032 /CISPR 32, EN55035/CISPR 35, EN63000, FCC pt15B, ICES003
<b>Other</b>	Cal Prop 65, China ROHS, EU REACH, UK REACH
<b>Packing Box</b>	
<b>Length (mm) / (in.)</b>	292 / 11.5
<b>Width (mm) / (in.)</b>	245 / 9.6
<b>Depth (mm) / (in.)</b>	55 / 2.2
<b>Weight (kg) / (lb)</b>	0.5 / 1.1



### What's in the Box?

1x IPEPS MINI unit with DP connector

### Ordering Information

IPEPSMINI-DP                      KVM-over-IP Extender with USB and DP video

### Related Accessories (Sold Separately)

ADDER® Power Supply Unit 5volt DC 2.5A

ADDER® PSU RED PRO 12V to 5V DC converter

ADDER® VSCD DisplayPort™ Cable

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.

Copyright 2025 | Adder Technology Ltd.