



A high-resolution, quad-head KVM extender. High-definition video, transparent full-speed USB 2.0 and audio are transmitted on a single CATx or fiber cable.

A high performance KVMA extender that is designed to provide reliable and real-time access to critical computers while maintaining the same user desktop experience. Developed for enterprise organizations and high-pressure control rooms, it combines the simplicity of true plug and play and high performance 4K KVM extension for superior functionality and flexibility.

ADDERLink® XD C650 R

Quad-Head High-Definition Video

Supports quad-head 1920x1200@60Hz or single head 4096x2160@60Hz (DCI 4K60). Quad-head enabled over a single cable using DisplayPort 1.2 Multi-Stream Transport (MST) technology.

Emulated and Hi-Speed USB 2.0

USB 2.0 emulation ensures reliable connection of full and low speed HID devices (mouse or keyboard). Mass storage devices and isochronous devices, such as webcams and audio headsets can also be used through the transparent USB 2.0 Hi-Speed port.

Digital Audio over DisplayPort

Supports two channels of 24-bit, 192kHz sampled PCM audio over the DisplayPort connection.

Up to 4km Extension

Supports both copper and fiber interfaces. Provides a range of up to 100m/328ft over a CAT6 cable link, and up to 4km/2.5 miles over an optical fiber link (Fiber SFP modules sold separately).

Plug and Play

Uses a low-latency point-to-point protocol over a single CATx or fiber cable that works as soon as it is connected. No network set-up, driver or software is required.

Analog Audio

Plug analog line in/out and headphones directly into the receiver. Audio is transmitted as bi-directional stereo 24-bit/96kHz using either an analog or USB connection to the host.



ADDER[®]

ADDERLink[®] XD C650 R



Monitor Flexibility

EDID management allows the monitor capabilities to be passed back to the host computer for optimum compatibility.

Serial communications

RS232 can be passed between the units to a maximum rate of 115200 baud with RTS/CTS flow control.

Video Information (1 Screen)

Maximum Resolution (1 Screen)	4096 x 2160
Frame Rate (1 Screen)	60 Hz
Color Depth (1 Screen)	8 bpc

Video Information (2 Screen)

Maximum Resolution (2 Screens)	2560 x 1600
Frame Rate (2 Screens)	60 Hz
Color Depth (2 Screen)	8 bpc

Video Information (3 Screen)

Maximum Resolution (3 Screens)	1920 x 1200
Frame Rate (3 Screens)	60 Hz
Color Depth (3 Screen)	8 bpc

Video Information (4 Screen)

Maximum Resolution (4 Screens)	1920 x 1200
Frame Rate (4 Screens)	60 Hz
Color Depth (4 Screen)	8 bpc

Video Additional Information

Video Additional Information	Supports HD60 Quad-Head or 4K60 Single-Head.
------------------------------	--

Console Connections

USB A	3x 2.0, True Emulation (HID Only),Full Speed
USB A	1x 2.0, Transparent,Full Speed
Full Size DisplayPort	2x 1.2

Link Ports

8p8c (RJ45)	1x
SFP+	1x

Serial Ports

Serial Connection	1x RS232
Maximum Baud Rate	115200
Serial Additional Information	With RTS/CTS flow control
Serial Connection Type (console)	RJ12 (6p6c)

Audio Connections

Audio Type	Analog/Digital
------------	----------------

Channels	2x
Audio Direction	Bi-directional
Audio Additional Information	Also supports 2 channels of 24-bit/192kHz PCM audio over the DisplayPort connection
Size (bit)	24
Speed (kHz)	96
Audio In Port	1x 3.5mm jack
Audio Out Port	2x 3.5mm jack

Cable Requirements

CAT5e	50m / 164ft
CAT6 (SFTP)	100m / 328ft
Fiber (MM)	400m / 1312ft
Fiber (SM)	4,000m / 13123ft

Network Support

10/100 Support	No
-----------------------	----

Power Source

12V 3-pin	1x
Input Power Supply	PSU 18W
Power Additional Information	100-240 VAC, 47/63Hz. 12 VDC 18W output from power supply unit

Physical Design

Construction Material	Robust metal construction
Width (mm) / (in.)	186 / 7.3
Height (mm) / (in.)	39 / 1.5
Depth (mm) / (in.)	148 / 5.8
Weight (kg) / (lb)	1.24 / 2.7

Front Panel Features

Multi color status LEDs

Compatibility

OS Compatibility	All known operating systems
-------------------------	-----------------------------



ADDERLink® XD C650 R

What's in the Box?

1x TX and RX pair

2x Power supply unit with country specific mains cable

1x DisplayPort® cable (VSCD18)

1x USB cable (VSC24)

1x Audio 2m/6ft cable

1x Quick start guide

Ordering Information

XD-C650P-DP-XX

ADDERLink HD quad-head transparent USB2.0 extender

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.