



A high-resolution single-head KVM extender. Ultra high-definition 4K60 video, USB 2.0 and audio are transmitted on a single CATx or fiber cable.

High performance KVMA extender that is designed to provide reliable and real-time access to critical computers - regardless of the location, while maintaining the same user desktop user experience.

## ADDERLink® XD641 T

### Single-Head DCI 4K60 Video

Supports single head 4096x2160@60Hz (DCI 4K60) with 24-bit colour and 4:4:4 chroma.

### Emulated USB 2.0

Emulation ensures reliable connection of up to four full and low speed HID devices, from mouse and keyboards through to graphics tablets and jog shuttles.

### Digital Audio over DisplayPort

Supports up to eight channels of 24-bit, 192kHz sampled PCM audio over the DisplayPort connection.

### Up to 4km Extension

Supports both copper and fiber interfaces. Provides a range of up to 100m/328ft over a CAT6 cable link, and up to 4km/2.5 miles over an optical fiber link (Fiber SFP modules sold separately).

### Plug and Play

Uses a low-latency point-to-point protocol over a single CATx or fiber cable that works as soon as it is connected. No network set-up, driver or software is required.

### Analog Audio

Plug analog line in/out and headphones directly into the receiver. Audio is transmitted as bi-directional stereo 24-bit/96kHz using either analog or USB connection to the host.



**ADDER**® ADDERLink® XD641 T



### Monitor Flexibility

EDID management allows the monitor capabilities to be passed back to the host computer for optimum compatibility. Additionally, a local monitor may be connected at the transmitter side.

### Serial communications

RS232 can be passed between the units to a maximum rate of 115200 baud with RTS/CTS flow control.

## Video Information (1 Screen)

**Maximum Resolution (1 Screen)** 4096 x 2160

**Frame Rate (1 Screen)** 60 Hz

**Color Depth (1 Screen)** 8 bpc

## Video Additional Information

**Video Additional Information** Transmitter features a local DisplayPort video pass through (Console Connection)

## Computer Connections

**USB B** 1x 2.0, True Emulation (HID Only),Full Speed

**USB B** 1x 2.0, True Emulation,Full Speed

**Full Size DisplayPort** 1x 1.2

## Console Connections

**Full Size DisplayPort** 1x 1.2

## Link Ports

**8p8c (RJ45)** 1x

**SFP+** 1x

## Serial Ports

**Serial Connection** 1x RS232

**Maximum Baud Rate** 115200

**Serial Additional Information** With RTS/CTS flow control

**Serial Connection Type (console)** RJ12 (6p6c)

## Audio Connections

**Audio Type** Analog/Digital

**Channels** 2x

**Audio Direction** Bi-directional

**Audio Additional Information** Also supports 8 channels of 24-bit/192kHz PCM audio over the DisplayPort connection. Analog audio can be connected to the host using analog or USB ports

**Size (bit)** 24

**Speed (kHz)** 96

**Audio In Port** 1x 3.5mm jack

**Audio Out Port** 1x 3.5mm jack

## Cable Requirements

<b>CAT5e</b>	50m / 164ft
<b>CAT6 (SFTP)</b>	100m / 328ft
<b>Fiber (MM)</b>	400m / 1312ft
<b>Fiber (SM)</b>	4,000m / 13123ft

#### Network Support

<b>10/100 Support</b>	No
-----------------------	----

#### Environmental

<b>Operating Temperature Range °C / °F</b>	0 to 40 °C / 32 to 104 °F
<b>Storage Temperature °C / °F Range</b>	-10 to 50 °C / 14 to 122 °F
<b>Operating Humidity (%)</b>	0% - 80% (non-condensing)
<b>Storage Humidity (%)</b>	0% - 80% (non-condensing)
<b>Altitude m/ft</b>	2,000 / 6562
<b>Mean Time Between Failure (MTBF)</b>	500,000 h
<b>MTBF Standard</b>	Telcordia SR332 Issue 4 March 2016 Calculated @ 55C
<b>Temperature Regulation</b>	Fanless

#### Power Source

<b>12V 3-pin</b>	1x
<b>Input Power Supply</b>	PSU 18W
<b>Power Additional Information</b>	100-240 VAC, 47/63Hz • 12 VDC 18W output from power supply unit

#### Physical Design

<b>Construction Material</b>	Robust metal construction
<b>Width (mm) / (in.)</b>	186 / 7.3
<b>Height (mm) / (in.)</b>	39 / 1.5
<b>Depth (mm) / (in.)</b>	148 / 5.8
<b>Weight (kg) / (lb)</b>	1.29 / 2.8

#### Front Panel Features

<b>Multi color status LEDs</b>	4x
--------------------------------	----

#### Compatibility

<b>OS Compatibility</b>	All known operating systems
-------------------------	-----------------------------

#### Approvals and Standards

<b>Approvals</b>	CE, cULus - E476334, FCC, ICES, RCM, UKCA
------------------	---

**Standards**

ANSI 63.4, EN/IEC 62368-1, EN55032 /CISPR 32,  
EN55035/CISPR 35, EN61000-3-2, EN61000-3-3, EN63000,  
FCC pt15B, ICES003

---

**Other**

Cal Prop 65, China ROHS, EU REACH, UK REACH

---



ADDERLink® XD641 T

#### What's in the Box?

1x TX and RX pair

2x Power supply unit with country specific mains cable

1x DisplayPort® cable (VSCD18)

1x USB cable (VSC24)

1x Audio 2m/6ft cable

1x Quick start guide

#### Ordering Information

XD641P-DP-XX

ADDERLink® 4K single-head extender

#### Related Accessories (Sold Separately)

ADDER® VSCD DisplayPort™ Cable

ADDER® SFP-SM-LC-10G

ADDER® SFP-MM-LC-10G

ADDER® Rackmount Kit RMK15-SH

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.