

**A high-resolution, dual-head KVM extender with DisplayPort connectivity. Ultra-high definition 4K60 video, USB2.0 and audio are transmitted on a single CATx or fiber cable.**

A high performance KVMA extender that is designed to provide reliable and real-time access to critical computers while maintaining the same user desktop experience. Developed for enterprise organizations and high-pressure control rooms, it combines the simplicity of true plug and play and high performance 4K KVM extension for superior functionality and flexibility.

## ADDERLink® XD642 T

### Dual-Head DCI 4K60 Video

Supports Dual-head 4096x2160@60Hz (DCI 4K60) with 24-bit colour and 4:4:4 chroma. A fiber connection is required for dual 4K60 operation, however dual 2560 x 1600@60Hz is supported over CATx cable.

### Emulated and Hi-Speed USB 2.0

USB 2.0 emulation ensures reliable connection of full and low speed HID devices (mouse or keyboard). Mass storage devices and isochronous devices, such as webcams and audio headsets can also be used through the transparent USB 2.0 Hi-Speed port.

### Digital Audio over DisplayPort

Supports up to eight channels of 24-bit, 192kHz sampled PCM audio over the DisplayPort connection.

### Up to 4km Extension

Supports both copper and fiber interfaces. Provides a range of up to 100m/328ft over a CAT6 cable link, and up to 4km/2.5 miles over an optical fiber link (Fiber SFP modules sold separately).

### Plug and Play

Uses a low-latency point-to-point protocol over a single CATx or fiber cable that works as soon as it is connected. No network set-up, driver or software is required.


### Analog Audio

Plug analog line in/out and headphones directly into the receiver. Audio is transmitted as bi-directional stereo 24-bit/96kHz using either analog or USB connection to the host.



**ADDER**<sup>®</sup>

ADDERLink<sup>®</sup> XD642 T



### Monitor Compatability

EDID management allows the monitor capabilities to be passed back to the host computer for optimum compatability.

### Serial communications

RS232 can be passed between the units to a maximum rate of 115200 baud with RTS/CTS flow control.

### Video Information (1 Screen)

<b>Maximum Resolution (1 Screen)</b>	4096 x 2160
<b>Frame Rate (1 Screen)</b>	60 Hz
<b>Color Depth (1 Screen)</b>	8 bpc

### Video Information (2 Screen)

<b>Maximum Resolution (2 Screens)</b>	4096 x 2160
<b>Frame Rate (2 Screens)</b>	60 Hz
<b>Color Depth (2 Screen)</b>	8 bpc

### Video Additional Information

<b>Video Additional Information</b>	2x 4K60 requires a fiber connection
-------------------------------------	-------------------------------------

### Computer Connections

<b>USB B</b>	1x 2.0, True Emulation (HID Only),Full Speed
<b>USB B</b>	1x 2.0, Transparent,High Speed
<b>Full Size DisplayPort</b>	2x 1.2

### Link Ports

<b>8p8c (RJ45)</b>	1x
<b>SFP+</b>	1x

### Serial Ports

<b>Serial Connection</b>	1x RS232
<b>Maximum Baud Rate</b>	115200
<b>Serial Additional Information</b>	with RTS/CTS flow control
<b>Serial Connection Type (console)</b>	RJ12 (6p6c)

### Audio Connections

<b>Audio Type</b>	Analog/Digital
<b>Channels</b>	2x
<b>Audio Direction</b>	Bi-directional
<b>Audio Additional Information</b>	Also supports 8 channels of 24-bit/192kHz PCM audio over the DisplayPort connection.
<b>Size (bit)</b>	24
<b>Speed (kHz)</b>	96
<b>Audio In Port</b>	1x 3.5mm jack
<b>Audio Out Port</b>	1x 3.5mm jack

Cable Requirements	
CAT5e	50m / 164ft
CAT6 (SFTP)	100m / 328ft
Fiber (MM)	400m / 1312ft
Fiber (SM)	4,000m / 13123ft
Network Support	
10/100 Support	No
Environmental	
Operating Temperature Range °C / °F	0 to 40 °C / 32 to 104 °F
Storage Temperature °C / °F Range	-10 to 50 °C / 14 to 122 °F
Operating Humidity (%)	0% - 80% (non-condensing)
Storage Humidity (%)	0% - 80% (non-condensing)
Altitude m/ft	2,000 / 6562
Mean Time Between Failure (MTBF)	500,000 h
MTBF Standard	Telcordia SR332 Issue 4 March 2016 Calculated @ 55C
Power Source	
12V 3-pin	1x
Input Power Supply	PSU 18W
Power Additional Information	100-240 VAC, 47/63Hz. 12 VDC 18W output from power supply unit
Physical Design	
Construction Material	Robust metal construction
Width (mm) / (in.)	186 / 7.3
Height (mm) / (in.)	39 / 1.5
Depth (mm) / (in.)	148 / 5.8
Weight (kg) / (lb)	1.29 / 2.8
Front Panel Features	
Multi color status LEDs	4x
Compatibility	
OS Compatibility	All known operating systems
Approvals and Standards	
Approvals	CE, cULus - E476334, FCC, ICES, RCM, UKCA

**Standards**

ANSI 63.4, EN/IEC 62368-1, EN55032 /CISPR 32,  
EN55035/CISPR 35, EN61000-3-2, EN61000-3-3, EN63000,  
FCC pt15B, ICES003

---

**Other**

Cal Prop 65, China ROHS, EU REACH, UK REACH

---



ADDERLink® XD642 T

#### What's in the Box?

1x TX and RX pair

2x Power supply unit with country specific mains cable

2x DisplayPort™ cable (VSCD18)

1x USB cable (VSC24)

1x 2m/6ft Audio cable

1x Quick start guide

#### Ordering Information

XD642-DP-XX

ADDERLink 4K dual-head extender

#### Related Accessories (Sold Separately)

ADDER® VSCD DisplayPort™ Cable

ADDER® SFP-SM-LC-10G

ADDER® SFP-MM-LC-10G

ADDER® Rackmount Kit RMK15-SH

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.