

fixed-mounted circuit breaker approved to UL489 3-pole, BG II,

Cat Number: 3WL5225-4FG32-4GN2



fixed-mounted circuit breaker approved to UL489 3-pole, BG II,  $I_n=2500A$  AC 50/60 Hz, IEC: to 690V, 100kA at 440V ul: to 600V, 100kA at 480V rear connection horizontal Overcurrent release ETU 45 LSING protection adjustable 0.4-1 in with display and cubicle bus with ground fault protection Opt.: Comm./measuring func./ZSS Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC With 1st auxiliary release Shunt release "F", F1 50/60 Hz 230 V AC/220 V DC, 100% on-load factor With 2nd auxiliary release "R", F3 Undervoltage, instant. 208-240 V AC, 220-250 V DC 2NO+2NC

#### Technical Specifications:

Article Number | 3WL5225-4FG32-4GN2

Product family | 3-pole

Product Lifecycle (PLM) | PM400:Phase Out Started

PLM Effective Date | Product phase-out since: 01.10.2023

Price Group | 12M

Surcharge for Raw Material | see also metal factor (further details are available on the help page)

Metal Factor | LAO-----

Export Control Regulations | ECCN : EAR99 / AL : N

Standard lead time ex-works | 25 Day(s)

Net Weight (kg) | 59,000 Kg

Package size unit of measure | Not available

Quantity Unit | 1 Piece

Packaging Quantity | 1

EAN | Not available

UPC | Not available

Commodity Code | 85362090

LKZ\_FDB/ CatalogID | LV10.1

Product Group | 3745

Group Code | P360

Country of origin | Czech Republic

Compliance with the substance restrictions according to RoHS directive | Given

Product class | C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation | No