



# 1901 PENDANT

Sleek, low glare, pendant

## FEATURES

|                        |             |
|------------------------|-------------|
| IP rating              | IP44        |
| CSP Switchable         | Single CCT  |
| Tiltable (°)           | Fixed       |
| UGR                    | UGR<16      |
| Dimmable Option        | Yes (1-10V) |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>90      |
| Colour Consistency     | SDCM3       |
| Emergency Option       | Yes         |
| Rotation angle (°)     | Fixed       |
| Pendant Cable Length   | 1,500 mm    |

## INSTALLATION INFORMATION

|                             |   |
|-----------------------------|---|
| Input                       | 220-240V AC                                     |
| Maximum Ambient Temperature | 40°C  |
| Weight                      | 450g  |
| Insulation Coverable        | No  |
| Inrush Current              | 10A/22ms  |
| Cut Out Size                | 65-68   |
| Construction Material       | Aluminium                                       |
| UK Bathroom Zone            | 1   |
| Maximum ceiling thickness   | 40 mm   |
| SELV                        | Yes   |
| Electric Class (1, 2, 3)    | II  |
| Suitable for coastal areas  | No  |
| Install Connector Type      | Loop in / Loop out                              |
| UK Building Regulations     | Part P, L, C & E                                |
| FR Building Regulations     | Satisfait les essais au fil incandescent: 650°C |
| Mounting Options            | Suspended                                       |
| Power Factor                | 0.80  |

## PHOTOMETRICS @ 25°C

| Product code | Finish                | Type                                      | W    | Colour | Beam | lm  | lm/W | Lx @ 1m | Energy |
|--------------|-----------------------|---|------|--------|------|-----|------|---------|--------|
| BPL15F27NM   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 15°  | 800 | 89   | 7214    |        |
| BPL15F27ND   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 15°  | 800 | 89   | 7214    |        |
| BPL15F27NV   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 15°  | 800 | 89   | 7214    |        |
| BPL15F27MM   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 24°  | 800 | 89   | 3250    |        |
| BPL15F27MD   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 24°  | 800 | 89   | 3250    |        |
| BPL15F27MV   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 24°  | 800 | 89   | 3250    |        |
| BPL15F27WM   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 50°  | 800 | 89   | 1300    |        |
| BPL15F27WD   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 50°  | 800 | 89   | 1300    |        |
| BPL15F27WV   | Matt white<br>RAL9003 | Pendant Black<br>Baffle Semi-<br>Recessed | 9.0W | 2700K  | 50°  | 800 | 89   | 1300    |        |

Semi-recessed for discreet  
look



Baffled for low glare and  
visual comfort

CRI 90 providing true colour  
appearance

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Available with a choice of a matt black or matt  
white finish

A sleek cylindrical style with hidden fixings

Complete with 1.5m adjustable fabric cable

7 year warranty: Collingwood's signature quality  
you can trust

**BPL15F30NM**Matt white  
RAL9003Pendant Black  
Baffle Semi-  
Recessed

9.0W

3000K

15°

800

89

7816



## WIRING INFORMATION

**Cable / Flying Lead** 2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)**Cable Required for Connector** 2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)**Type of Wiring Required** Parallel

## ACCESSORIES

**LEDEP10** 3hr non-maintained emergency pack (plug & play) Sold Separately**BDLFH2** Fire Hood Sold Separately**COLLINGWOOD**  
LIGHTING

### LIGHTING INNOVATION

More than a century of design and innovation helped inspire the creation of the luxurious architectural 1901 range, for when only the best will do. 1901 is both contemporary and classic, with a focus on premium fittings, a high-quality performance and easy integration into control systems. Perfect for luxury residential and hospitality projects, 1901 showcases an aesthetically simple, low-glare luminaire design, with market-leading technical performance. The detailed fittings come in a variety of stylish options including a choice of bezels, adjustability, colour temperatures, beam angles, dimming methods, and IP ratings to perfectly complete the look of any interior design project. Simply configure your product to find the relevant product code. The range is engineered to be as easy to use as possible and can fit seamlessly into the installation and commissioning stages of a lighting project.